

CTP pin

PIN No.	Symbol
1	GND
2	INT(3.3V)
3	RST(3.3V)
4	VDD(3.3V)
5	SCL(3.3V)
6	SDA(3.3V)


EPD pin

PIN No.	Symbol
1	NC
2	GDR
3	RESE
4	NC
5	VSH2
6	TSCL
7	TSDA
8	BS1
9	BUSY
10	RST#
11	D/C#
12	CS#
13	SCL
14	SDA
15	VDDIO
16	VCI
17	VSS
18	VDD
19	VPP
20	VSH1
21	VGH
22	VSL
23	VGL
24	VCOM

LED pin

PIN No.	Symbol
1	LED+
2	LED+
3	NC
4	NC
5	LED-
6	LED-

LED CIRCUIT DIAGRAM (LED 1\*4=4 DIES)



Vf=2.75V min 2.9V typ 3.0V max  
If=60mA

1	Display mode	EPD,B/W
2	Resolution ratio	2.9",128*296
3	Operating Voltage:	VCI=3.0V
4	Operating Temp:	0°C~50°C
5	Storage Temp:	-25°C~70°C
6	controller/driver:	SSD1680
7	CTP controller/driver	FT6336U
8	Unspecified tolerance:	±0.2
9	Customer No.:	
10	Dimensions with mark "*" are important	
11	RoHS compliant	

NO.	REVISION RECORD	NAME	DATE	DALIAN GOOD DISPLAY CO., LTD	
3				GDEY029T94-FT01	Drw YC 2023.9.1
2				Unit: mm	Chk
1	Initial version.				Apv