

1	NC
2	GDR
3	RESE
4	NC
5	VDHR
6	TJCL
7	TSDA
8	BS
9	BUSY_N
10	RST_N
11	D/C
12	CSB
13	SCL
14	SDA
15	VDD10
16	VDD
17	GND
18	VDDD
19	VPP
20	VSH
21	VGH
22	VSL
23	VGL
24	VCOM

CTP PIN

PIN	1	2	3	4	5	6
(AND)	VDD (3.30V)	RST (3.30V)	INT (3.30V)	SNA (3.30V)	SCL (3.30V)	SCL (3.30V)

1	Display mode	EPD_B/W
2	Resolution ratio	3.7" 240*416
3	Operating Voltage:	VDD=3.0V
4	Operating Temp:	0°C~50°C
5	Storage Temp:	-25°C~70°C
6	controller/driver:	UC8253
7	CTP DRIVER IC	PT6336U
8	Unspecified tolerance:	±0.3
9	Customer No.:	
10	Dimensions with mark	* are important
11	RoHS compliant	


REVISION RECORD

NO.	DATE
1	2023.02.27
2	
3	

DALIAN GOOD DISPLAY CO., LTD

GDEY037T03-T02

Drw




Unit:mm

Chk

1/1 Imit version(Modify sensor on 037BAA-W1-SA)

2023.02.27



Appv