



2.66 inch E-paper Display Series

GDEY0266F52H

Dalian Good Display Co., Ltd.



Product Specifications



| | |
|--------------------|-----------------------------|
| Customer | Standard |
| Description | 2.66" EPAPER DISPLAY |
| Model Name | GDEY0266F52H |
| Date | 2025/07/17 |
| Revision | 1.0 |

| | Design Engineering | | |
|--|---|---|---|
| | Approval | Check | Design |
| |  |  |  |

No.18, Zhonghua West ST,Ganjingzi DST,Dalian,CHINA

Tel: +86-411-84619565

Email: info@good-display.com

Website: www.good-display.com

CONTENTS

| | |
|--|----|
| 1. Over View..... | 5 |
| 2. Features | 5 |
| 3. Mechanical Specification..... | 5 |
| 4. Mechanical Drawing of EPD Module..... | 6 |
| 5. Input/output Pin Assignment..... | 7 |
| 6. Electrical Characteristics..... | 8 |
| 6.1 Absolute Maximum Rating..... | 8 |
| 6.2 Panel DC Characteristics..... | 9 |
| 6.3 Panel AC Characteristics..... | 10 |
| 6.3.1 MCU Interface Selection..... | 10 |
| 6.3.2 MCU Serial Interface (4-wire SPI)..... | 10 |
| 6.3.3 MCU Serial Interface (3-wire SPI)..... | 11 |
| 7. Command Table..... | 12 |
| 8. Handling, Safety, and Environment Requirements..... | 34 |
| 9. Reliability Test..... | 35 |

| | |
|----------------------------------|----|
| 10. Reference Circuit..... | 36 |
| 11. Matched Development Kit..... | 37 |
| 12. Inspection condition..... | 38 |
| 13. Packaging..... | 42 |
| 14. Precautions..... | 43 |

GOODDISPLAY

1. Over View

GDEY0266F51H is a reflective electrophoretic technology display module on an active matrix TFT substrate. The panel is capable of displaying black, white, yellow and red images depending on the associated look-up table used. The circuitry on the panel includes an integrated gate and source driver, timing controller, oscillator, DC-DC boost circuit, and memory to store the frame buffer and look-up tables, and additional circuitry to control VCOM and BORDER settings.


2. Features

- Highlight Red and Yellow
- color High contrast
- High reflectance
- Ultra wide viewing angle
- Ultra low power consumption
- Pure reflective mode
- Bi-stable display
- Antiglare hard-coated
- front-surface Low current deep sleep mode
- On chip display RAM
- Waveform stored in On-chip
- OTP Serial peripheral interface
- On-chip oscillator and regulator control for generating VCOM, Gate and Source driving voltage
- I²C signal master interface to read external temperature
- sensor Available in COG package

3. Mechanical Specifications

| Parameter | Specifications | Unit | Remark |
|---------------------|---------------------------|-------|---------|
| Screen Size | 2.66 | Inch | |
| Display Resolution | 184(H)×360(V) | Pixel | PPI:152 |
| Active Area | 30.69×60.05 | mm | |
| Pixel Pitch | 0.1668×0.1668 | mm | |
| Pixel Configuration | Rectangle | | |
| Outline Dimension | 37.11(H)×72.59(V) ×1.0(D) | mm | |
| Weight | 5.05±0.5 | g | |

4. Mechanical Drawing of EPD module



5. Input /Output Pin Assignment

| No. | Name | I/O | Description | Remark |
|-----|---------|-----|--|-----------|
| 1 | NC | | Do not connect with other NC pins | Keep Open |
| 2 | GDR | O | This pin is N-MOS gate control. | |
| 3 | RESE | P | Current sense input for control loop. | |
| 4 | NC | | Do not connect with other NC pins | Keep Open |
| 5 | VSPL | P | Positive source voltage | |
| 6 | TSCL | O | I ² C clock for external temperature sensor (I ² C interface need external pull high resistance.) Must pull high or low if not used. | |
| 7 | TSDA | I/O | I ² C data for external temperature sensor (I ² C interface need external pull high resistance.) Must pull high or low if not used.(Default low) | |
| 8 | BS | I | Input interface setting. | |
| 9 | BUSY_N | O | This pin indicates the driver status. | |
| 10 | RST_N | I | Global reset pin. Low reset. (normal pull high) | |
| 11 | DC | I | Serial communication Command/Data input | |
| 12 | CSB | I | Serial communication chip select. | |
| 13 | SCL | I | Serial communication clock input. | |
| 14 | SDA | I/O | Serial communication data input. | |
| 15 | VDDIO | P | IO voltage supply | |
| 16 | VDD | P | Digital/Analog power. | |
| 17 | VSS | P | Ground | |
| 18 | VDD_15V | P | 1.5V voltage input & output | |
| 19 | VMTP | P | MTP program power | |
| 20 | VSP | P | Positive source voltage | |
| 21 | VGP | P | Positive gate voltage | |
| 22 | VSN | P | Negative Source driving voltage | |
| 23 | VGN | P | Negative gate voltage | |
| 24 | VCOM | O | VCOM driving voltage | |

Note: I: Input, O: Output, P: Power, D: Dummy, S: Shorted line, M: Mark, PI: Power input, PO: Power output, I/O: Input / Output. PS: Power Setting, C: Capacitor pin.

6. Electrical Characteristics

6.1 Absolute Maximum Rating


| Parameter | Symbol | Rating | Unit |
|--------------------------|---------------------------------|-------------------|------|
| Logic supply voltage | VDD, AVDD,VDDIO, VDD1,VPP | -0.3 to +6.0 | V |
| Logic Input voltage | VI | -0.3 to VDDIO+0.3 | V |
| Operating Temp range | TOPR | 0 to +40 | °C |
| Storage Temp range | TSTG | -25 to +70 | °C |
| Optimal Storage Temp | TSTGo | 23±2 | °C |
| Optimal Storage Humidity | HSTGo | 55±10 | %RH |

Note: Absolute Maximum Ratings are stress ratings. Stresses in excess of these ratings can cause permanent damage to the device. Functional operation of the device at these or any other conditions beyond those indicated in the operational sections of this data sheet is not implied. Exposing device to the absolute maximum ratings in a long period of time may degrade the device and affect its reliability.

6.2 Panel DC Characteristics

| Parameter | Symbol | Conditions | Applicable pin | Min. | Typ. | Max | Units |
|---------------------------|----------------------|--------------------------|-----------------|----------------------|-------|--------------------|-------|
| Single ground | V _{SS} | - | | - | 0 | - | V |
| Logic supply voltage | V _{IO} | - | V _{IO} | 2.3 | 3.3 | 3.6 | V |
| Core logic voltage | V _{DD} | - | V _{DD} | 2.3 | 3.3 | 3.6 | V |
| High level input voltage | V _{IH} | - | - | 0.7V _{IO} | - | V _{IO} | V |
| Low level input voltage | V _{IL} | - | - | GND | - | 0.3V _{DD} | V |
| High level output voltage | V _{OH} | I _{OH} = 400uA | - | V _{IO} -0.4 | - | - | V |
| Low level output voltage | V _{OL} | I _{OL} = -400uA | - | GND | - | GND +0.4 | V |
| Typical power | P _{TYP} | V _{DD} =3.3V | - | - | 18.48 | - | mW |
| Deep sleep mode | P _{STPY} | V _{DD} =3.3V | - | - | 0.003 | - | mW |
| Typical operating current | I _{opr_VDD} | V _{DD} =3.3V | - | - | 5.6 | - | mA |
| Image update time | - | 25 °C | - | - | 26 | - | sec |
| Stand-by current | I _{st_VDD} | | - | - | 1 | 5 | uA |

Notes: 1. The typical power is measured with following transition from horizontal 4 scale pattern to vertical 4 scale pattern.




2. The deep sleep power is the consumed power when the panel controller is in deep sleep mode.
3. The listed electrical/optical characteristics are only guaranteed under the controller & waveform provided by NEWFACE.
4. Electrical measurement: Multimeter

6.3 AC Characteristics


6.3.1 MCU Interface Selection

The 3-wire/4-wire serial port as communication interface for all the function and command setting. 3-wire/4-wire engine act as a "slave mode" for all the time, and will not issue any command to the 3-wire/4-wire bus itself. Under read mode, 3-wire/4-wire engine will return the data during "Data phase". The returned data should be latched at the rising edge of SCL by external controller. Data in the "Hi-Z phase" will be ignored by 3-wire/4-wire engine during write operation, and should be ignored during read operation also. During read operation, external controller should float SDA pin under "Hi-Z phase" and "Data phase".


6.3.2 MCU Serial Interface (4-wire SPI)




4 pin serial interface characteristics(write mode)




4 pin serial interface characteristics(read mode)




6.3.3 MCU Serial Interface (3-wire SPI)



3 pin serial interface characteristics (write mode)



3 pin serial interface characteristics (read mode)



7. Command Table

| Address | command | Bit | | | | | | | | | | |
|---------|--------------------------------------|-----|------|-----------|-----------|-----------|-----------|--------------|--------------|-----------|-----------|------|
| | | R/W | D/CX | D7 | D6 | D5 | D4 | D3 | D2 | D1 | D0 | Code |
| R00H | Panel setting (PSR) | W | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 00H |
| | | W | 1 | RES[1] | RES[0] | PST_MODE | - | UD | SHL | SHD_N | RST_N | 0Fh |
| | | W | 1 | LUT_EN | - | FOPT | VCMZ | TS_AUTO | TIEG | NORG | VC_LUTZ | 09h |
| R01H | Power setting (PWR) | W | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 01H |
| | | W | 1 | - | - | - | - | - | VSC_EN | VDS_EN | VDG_EN | 07h |
| | | W | 1 | - | - | - | - | - | - | VGPN[1] | VGPN[0] | 00h |
| | | W | 1 | - | VSPL_0[6] | VSPL_0[5] | VSPL_0[4] | VSPL_0[3] | VSPL_0[2] | VSPL_0[1] | VSPL_0[0] | 00h |
| | | W | 1 | - | VSP_1[6] | VSP_1[5] | VSP_1[4] | VSP_1[3] | VSP_1[2] | VSP_1[1] | VSP_1[0] | 00h |
| | | W | 1 | - | VSN_1[6] | VSN_1[5] | VSN_1[4] | VSN_1[3] | VSN_1[2] | VSN_1[1] | VSN_1[0] | 00h |
| | | W | 1 | - | VSPL_1[6] | VSPL_1[5] | VSPL_1[4] | VSPL_1[3] | VSPL_1[2] | VSPL_1[1] | VSPL_1[0] | 00h |
| R02H | Power OFF(POF) | W | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 0 | 02H |
| | | W | 1 | - | - | - | - | - | - | - | - | 00h |
| R04H | Power ON (PON) | W | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 04H |
| R06H | Booster Soft Start (BTST) | W | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 1 | 0 | 06H |
| | | W | 1 | - | - | - | - | PHB_SFT[1:0] | PHA_SFT[1:0] | | | 00h |
| | | W | 1 | - | - | - | - | PHA_ON[5:0] | | | | 02h |
| | | W | 1 | - | - | - | - | PHA_OFF[5:0] | | | | 07h |
| | | W | 1 | - | - | - | - | PHB_ON[5:0] | | | | 02h |
| | | W | 1 | - | - | - | - | PHB_OFF[5:0] | | | | 07h |
| | | W | 1 | - | - | - | - | PHC_ON[5:0] | | | | 02h |
| | | W | 1 | - | - | - | - | PHC_OFF[5:0] | | | | 07h |
| R07H | Deep Sleep(DSLP) | W | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 1 | 1 | 07H |
| | | W | 1 | 1 | 0 | 1 | 0 | 0 | 1 | 0 | 1 | A5h |
| R10H | Data Start transmission (DTM) | W | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 10H |
| | | W | 1 | # | # | # | # | # | # | # | # | 00H |
| R11H | Data Stop (DSP) | W | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 1 | 11H |
| | | R | 1 | Data_flag | - | - | - | - | - | - | - | -- |
| R12H | Display Refresh (DRF) | W | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 1 | 0 | 12H |
| | | W | 1 | - | - | - | - | - | - | - | - | 00H |
| R17H | Auto sequence (AUTO) | W | 0 | 0 | 0 | 0 | 1 | 0 | 1 | 1 | 1 | 17H |
| | | W | 1 | Code[7] | Code[6] | Code[5] | Code[4] | Code[3] | Code[2] | Code[1] | Code[0] | A5h |
| R30H | PLL control (PLL) | W | 0 | 0 | 0 | 1 | 1 | 0 | 0 | 0 | 0 | 30H |
| | | W | 1 | - | - | - | - | Dyna | FR[2:0] | | | 02h |
| R40H | Temperature Sensor Command (TSC) | W | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 40H |
| | | R | 1 | D10/TS[7] | D9/TS[7] | D8/TS[6] | D7/TS[5] | D6/TS[4] | D5/TS[3] | D4/TS[2] | D3/TS[1] | -- |
| | | R | 1 | D2/TS[9] | D1/TS[8] | D0 | - | - | - | - | - | -- |
| R41H | Temperature Sensor Calibration (TSE) | W | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 1 | 41H |
| | | W | 1 | TSE | - | - | TO[4] | TO[3] | TO[2] | TO[1] | TO[0] | 00h |
| R42H | Temperature Sensor Write (TSW) | W | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 1 | 0 | 42H |
| | | W | 1 | WATTR[7] | WATTR[6] | WATTR[5] | WATTR[4] | WATTR[3] | WATTR[2] | WATTR[1] | WATTR[0] | 00h |
| | | W | 1 | WMSB[7] | WMSB[6] | WMSB[5] | WMSB[4] | WMSB[3] | WMSB[2] | WMSB[1] | WMSB[0] | 00h |
| | | W | 1 | WLSB[7] | WLSB[6] | WLSB[5] | WLSB[4] | WLSB[3] | WLSB[2] | WLSB[1] | WLSB[0] | 00h |
| R43H | Temperature Sensor Read (TSR) | W | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 1 | 1 | 43H |
| | | R | 1 | RMSB[7] | RMSB[6] | RMSB[5] | RMSB[4] | RMSB[3] | RMSB[2] | RMSB[1] | RMSB[0] | -- |
| | | R | 1 | RLSB[7] | RLSB[6] | RLSB[5] | RLSB[4] | RLSB[3] | RLSB[2] | RLSB[1] | RLSB[0] | -- |
| R50H | VCOM and DATA interval setting (CDI) | W | 0 | 0 | 1 | 0 | 1 | 0 | 0 | 0 | 0 | 50H |
| | | W | 1 | VBD[2] | VBD[1] | VBD[0] | DDX | CDI[3] | CDI[2] | CDI[1] | CDI[0] | 97h |

| | | | | | | | | | | | | | |
|------|---------------------------------|---|---|------------|------------|------------|------------|------------|------------|-------------|-------------|-----|-----|
| R51H | Lower Power Detection (LPD) | W | 0 | 0 | 1 | 0 | 1 | 0 | 0 | 0 | 1 | 51H | |
| | | R | 1 | - | - | - | - | - | - | - | LPD | -- | |
| R61H | Resolution setting(TRES) | W | 0 | 0 | 1 | 1 | 0 | 0 | 0 | 0 | 1 | 61H | |
| | | W | 1 | - | - | - | - | - | - | HRES(9) | HRES(8) | 00h | |
| | | W | 1 | HRES(7) | HRES(6) | HRES(5) | HRES(4) | HRES(3) | HRES(2) | 0 | 0 | 00h | |
| | | W | 1 | - | - | - | - | - | - | VRES(9) | VRES(8) | 00h | |
| | | W | 1 | VRES(7) | VRES(6) | VRES(5) | VRES(4) | VRES(3) | VRES(2) | VRES(1) | VRES(0) | 00h | |
| R65H | Gate/Source Start Setting(GSST) | W | 0 | 0 | 1 | 1 | 0 | 0 | 1 | 0 | 1 | 65H | |
| | | W | 1 | - | - | - | - | - | - | S_start(9) | S_start(8) | 00h | |
| | | W | 1 | S_start(7) | S_start(6) | S_start(5) | S_start(4) | S_start(3) | S_start(2) | 0 | 0 | 00h | |
| | | W | 1 | - | - | - | - | - | - | G_start(9) | G_start(8) | 00h | |
| | | W | 1 | G_start(7) | G_start(6) | G_start(5) | G_start(4) | G_start(3) | G_start(2) | G_start(1) | G_start(0) | 00h | |
| R70H | REVISION (REV) | W | 0 | 0 | 1 | 1 | 1 | 0 | 0 | 0 | 0 | 70H | |
| | | R | 1 | 1 | 0 | 0 | 0 | 0 | 0 | 1 | 1 | 85h | |
| | | R | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 0 | 02h |
| | | R | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 01h |
| R80H | Auto Measure Vcom (AMV) | W | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 80H | |
| | | W | 1 | P[1] | P[0] | AMVT[1] | AMVT[0] | XON | AMVS | AMV | AMVE | 00h | |
| R81H | Vcom Value (VV) | W | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 81H | |
| | | R | 1 | - | VV[6] | VV[5] | VV[4] | VV[3] | VV[2] | VV[1] | VV[0] | -- | |
| R82H | Vcom_DC Setting register(VDCS) | W | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 1 | 0 | 82H | |
| | | W | 1 | MTP_VCM | VDCS[6] | VDCS[5] | VDCS[4] | VDCS[3] | VDCS[2] | VDCS[1] | VDCS[0] | 00h | |
| R83H | Partial Window (PTLW) | W | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 1 | 1 | 83H | |
| | | W | 1 | - | - | - | - | - | - | HRST(9) | HRST(8) | 00h | |
| | | W | 1 | HRST(7) | HRST(6) | HRST(5) | HRST(4) | HRST(3) | HRST(2) | 0 | 0 | 00h | |
| | | W | 1 | - | - | - | - | - | - | HRED(9) | HRED(8) | 00h | |
| | | W | 1 | HRED(7) | HRED(6) | HRED(5) | HRED(4) | HRED(3) | HRED(2) | 0 | 0 | 00h | |
| | | W | 1 | - | - | - | - | - | - | VRST(9) | VRST(8) | 00h | |
| | | W | 1 | VRST(7) | VRST(6) | VRST(5) | VRST(4) | VRST(3) | VRST(2) | VRST(1) | VRST(0) | 00h | |
| | | W | 1 | - | - | - | - | - | - | VRST(9) | VRST(8) | 00h | |
| | | W | 1 | VRST(7) | VRST(6) | VRST(5) | VRST(4) | VRST(3) | VRST(2) | VRST(1) | VRST(0) | 00h | |
| | | W | 1 | - | - | - | - | - | - | - | PMOD | 00h | |
| R90H | Program mode(PGM) | W | 0 | 1 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 90H | |
| R91H | Active Program(APG) | W | 0 | 1 | 0 | 0 | 1 | 0 | 0 | 0 | 1 | 91H | |
| R92H | Read MTP data (RMTP) | W | 0 | 1 | 0 | 0 | 1 | 0 | 0 | 1 | 0 | 92H | |
| | | R | 1 | # | # | # | # | # | # | # | # | - | |
| R9FH | Read MTP Reserved Bytes(RMRB) | W | 0 | 1 | 0 | 0 | 1 | 1 | 1 | 1 | 1 | 9FH | |
| | | R | 1 | # | # | # | # | # | # | # | # | - | |
| RE3H | Power saving(PWS) | W | 0 | 1 | 1 | 1 | 0 | 0 | 0 | 1 | 1 | E3H | |
| | | W | 1 | VCOM_W [3] | VCOM_W [2] | VCOM_W [1] | VCOM_W [0] | SD_W[3] | SD_W[2] | SD_W[2] | SD_W[0] | 00h | |
| RE4H | LVD voltage Select(LVSEL) | W | 0 | 1 | 1 | 1 | 0 | 0 | 1 | 0 | 0 | E4H | |
| | | W | 1 | - | - | - | - | - | - | LVD_SEL [1] | LVD_SEL [0] | 03h | |

| R00H | | | Bit | | | | | | | | |
|---------------------------|-----|------|--------|--------|----------|------|---------|------|-------|---------|------|
| Inst/Para | R/W | D/CX | D7 | D6 | D5 | D4 | D3 | D2 | D1 | D0 | Code |
| PSR | W | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 00H |
| 1 st Parameter | W | 1 | RES[1] | RES[0] | PST_MODE | - | UD | SHL | SHD_N | RST_N | 0Fh |
| 2 nd Parameter | W | 1 | LUT_EN | - | FOPT | VCMZ | TS_AUTO | TIEG | NORG | VC_LUTZ | 09h |

NOTE: "-" Don't care, can be set to VDD or GND level

| Description | -The command defines as : | | |
|-------------|---------------------------|--|---|
| | 1 st parameter | | |
| | Bit | Name | Description |
| | 0 | RST_N | RST_N function 1: no effect. (default) 0: Booster OFF, Register data are set to their default values, and Source/Boder/Vcom: floating |
| | 1 | SHD_N | SHD_N function 0 : Booster OFF, register data are kept, and Source/Boder/Vcom are kept 0V or floating. 1 : Booster on. (default) |
| | 2 | SHL | SHL function 0: Shift left; First data=Sn→Sn-1 →...→S2→Last data=S1. 1: Shift right: First data=S1→S2 →...→Sn-1→Last data=Sn. (default) |
| | 3 | UD | UD function 0:Scan down; First line=Gn→Gn-1 →...→G2→Last line=G1. 1:Scan up; First line=G1→G2 →...→Gn-1→Last line=Gn. (default) |
| | 5 | PST_MODE | Power switch operation mode 0:Power switching time in the period of frame scanning.(default) 1:Power switching time in the external period before frame scanning. |
| 7-6 | RES[1,0] | Resolution setting 00: Display resolution is 200x384 (default) 01: Display resolution is 184x384 10: Display resolution is 168x384 11: Display resolution is 200x200 | |

| 2 nd parameter | | |
|---------------------------|---------|---|
| Bit | Name | Description |
| 0 | VC_LUTZ | VCOM status function 0 : No effect 1 : After refreshing display, the output of VCOM is set to floating automatically (default) |
| 1 | NORG | VCOM status function 0 : No effect (default) 1 : After refreshing display, VCOM is tied to GND before power off |
| 2 | TIEG | VGN power off status function 0 : No effect (default) 1 : Power off, VGN will be tied to GND |
| 3 | TS_AUTO | Temperature sensing will be activated automatically one time 0 : Before enabling booster, Temperature Sensor will be activated automatically one time. 1 : When RST_N low to high, Temperature Sensor will be activated automatically one time. (default) |
| 4 | VCMZ | VCOM status function 0 : No effect (default) 1 : VCOM is always floating |
| 5 | FOPT | FOPT function 0: Scan 1 frame after waveform finished(default) 1: No scan after waveform finished and switch the source channel output to Hiz. |
| 7 | LUT_EN | LUT selection setting 0 : Using LUT from MTP(default) 1 : Using LUT from register |

Priority of VCOM setting: VCMZ > NORG > FOPT > VC_LUTZ

FOPT setting is part of refreshing display.
FOPT: Power off floating.

| | |
|-------------|--|
| | <p>Notes:</p> <ol style="list-style-type: none"> 1. Non-select gate line keep at VGN for DSP/DRF and AMV 2. Dummy source line follow LUTC for DSP/DRF 3. When SHD_N become low, DCDC will turn off. Register and SRAM data will keep until VDD turn off.SD output and VCOM will base on previous condition. It may have two condition:0V or floating. 4. When RST_N become low, driver will reset. All register will reset to default value. All of the driver's functions will disable. Source/Gate/Border/VCOM will be released to floating |
| Restriction | |

| R01H | Bit | | | | | | | | | | | |
|---------------------------|-----|------|----|--------------|----|----|----|--------|----------|----------|------|-----|
| Inst/Para | R/W | D/CX | D7 | D6 | D5 | D4 | D3 | D2 | D1 | D0 | Code | |
| PWR | W | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 01h | |
| 1 st Parameter | W | 1 | - | - | - | - | - | VSC_EN | VDS_EN | VDG_EN | 07h | |
| 2 nd Parameter | W | 1 | - | - | - | - | - | - | VGPN [1] | VGPN [0] | 00h | |
| 3 rd Parameter | W | 1 | - | VSPL_0 [6:0] | | | | | | | | 00h |
| 4 th Parameter | W | 1 | - | VSP_1 [6:0] | | | | | | | | 00h |
| 5 th Parameter | W | 1 | - | VSN_1 [6:0] | | | | | | | | 00h |
| 6 th Parameter | W | 1 | - | VSPL_1 [6:0] | | | | | | | | 00h |

NOTE: "-" Don't care, can be set to VDD or GND level

| Description | <p>-The command defines as :</p> <p>1st Parameter:</p> <table border="1"> <thead> <tr> <th>Bit</th> <th>Name</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>0</td> <td>VDG_EN</td> <td>Gate power selection. 0 : External gate power from VGP/VGN pins. 1 : Internal DCDC function for generate VGP/VGN. (default)</td> </tr> <tr> <td>1</td> <td>VDS_EN</td> <td>Source power selection. 0 : External source power from VSP/VSN pins. 1 : Internal regulator function for generate VSP/VSN (default)</td> </tr> <tr> <td>2</td> <td>VSC_EN</td> <td>Source LV power selection. 0 : External source power from VSPL pins. 1 : Internal regulator function for generate VSPL (default)</td> </tr> <tr> <td>3</td> <td>V_MODE</td> <td>Source Power switching mode. 0: Mode0(default) 1: Mode1</td> </tr> </tbody> </table> <p>2nd Parameter:</p> <table border="1"> <thead> <tr> <th>Bit</th> <th>Name</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>1-0</td> <td>VGPN</td> <td>VGPN Voltage Level. 00: VGP=20 v, VGN=-20v (default) 01: VGP=17 v, VGN=-17v 10: VGP=15 v, VGN=-15v 11: VGP=10 v, VGN=-10v</td> </tr> </tbody> </table> | | Bit | Name | Description | 0 | VDG_EN | Gate power selection. 0 : External gate power from VGP/VGN pins. 1 : Internal DCDC function for generate VGP/VGN. (default) | 1 | VDS_EN | Source power selection. 0 : External source power from VSP/VSN pins. 1 : Internal regulator function for generate VSP/VSN (default) | 2 | VSC_EN | Source LV power selection. 0 : External source power from VSPL pins. 1 : Internal regulator function for generate VSPL (default) | 3 | V_MODE | Source Power switching mode. 0: Mode0(default) 1: Mode1 | Bit | Name | Description | 1-0 | VGPN | VGPN Voltage Level. 00: VGP=20 v, VGN=-20v (default) 01: VGP=17 v, VGN=-17v 10: VGP=15 v, VGN=-15v 11: VGP=10 v, VGN=-10v |
|-------------|--|---|-----|------|-------------|---|--------|---|---|--------|---|---|--------|--|---|--------|---|-----|------|-------------|-----|------|---|
| Bit | Name | Description | | | | | | | | | | | | | | | | | | | | | |
| 0 | VDG_EN | Gate power selection. 0 : External gate power from VGP/VGN pins. 1 : Internal DCDC function for generate VGP/VGN. (default) | | | | | | | | | | | | | | | | | | | | | |
| 1 | VDS_EN | Source power selection. 0 : External source power from VSP/VSN pins. 1 : Internal regulator function for generate VSP/VSN (default) | | | | | | | | | | | | | | | | | | | | | |
| 2 | VSC_EN | Source LV power selection. 0 : External source power from VSPL pins. 1 : Internal regulator function for generate VSPL (default) | | | | | | | | | | | | | | | | | | | | | |
| 3 | V_MODE | Source Power switching mode. 0: Mode0(default) 1: Mode1 | | | | | | | | | | | | | | | | | | | | | |
| Bit | Name | Description | | | | | | | | | | | | | | | | | | | | | |
| 1-0 | VGPN | VGPN Voltage Level. 00: VGP=20 v, VGN=-20v (default) 01: VGP=17 v, VGN=-17v 10: VGP=15 v, VGN=-15v 11: VGP=10 v, VGN=-10v | | | | | | | | | | | | | | | | | | | | | |

3rd & 4th & 6th Parameter: Internal VSP_1/VSPL_0/ VSPL_1 power selection

| Bit | Name | Description | | | | | |
|---|------|-------------|------------|-----------|------------|-----------|------------|
| Internal VSP & VSPL power selection. | | | | | | | |
| | | bit[6:0] | Voltage(V) | bit [6:0] | Voltage(V) | bit [6:0] | Voltage(V) |
| | | 0000000 | 00h 3 | 0101001 | 29h 7.1 | 1010010 | 52h 11.2 |
| | | 0000001 | 01h 3.1 | 0101010 | 2Ah 7.2 | 1010011 | 53h 11.3 |
| | | 0000010 | 02h 3.2 | 0101011 | 2Bh 7.3 | 1010100 | 54h 11.4 |
| | | 0000011 | 03h 3.3 | 0101100 | 2Ch 7.4 | 1010101 | 55h 11.5 |
| | | 0000100 | 04h 3.4 | 0101101 | 2Dh 7.5 | 1010110 | 56h 11.6 |
| | | 0000101 | 05h 3.5 | 0101110 | 2Eh 7.6 | 1010111 | 57h 11.7 |
| | | 0000110 | 06h 3.6 | 0101111 | 2Fh 7.7 | 1011000 | 58h 11.8 |
| | | 0000111 | 07h 3.7 | 0110000 | 30h 7.8 | 1011001 | 59h 11.9 |
| | | 0001000 | 08h 3.8 | 0110001 | 31h 7.9 | 1011010 | 5Ah 12 |
| | | 0001001 | 09h 3.9 | 0110010 | 32h 8 | 1011011 | 5Bh 12.1 |
| | | 0001010 | 0Ah 4 | 0110011 | 33h 8.1 | 1011100 | 5Ch 12.2 |
| | | 0001011 | 0Bh 4.1 | 0110100 | 34h 8.2 | 1011101 | 5Dh 12.3 |
| | | 0001100 | 0Ch 4.2 | 0110101 | 35h 8.3 | 1011110 | 5Eh 12.4 |
| | | 0001101 | 0Dh 4.3 | 0110110 | 36h 8.4 | 1011111 | 5Fh 12.5 |
| | | 0001110 | 0Eh 4.4 | 0110111 | 37h 8.5 | 1100000 | 60h 12.6 |
| | | 0001111 | 0Fh 4.5 | 0111000 | 38h 8.6 | 1100001 | 61h 12.7 |
| | | 0010000 | 10h 4.6 | 0111001 | 39h 8.7 | 1100010 | 62h 12.8 |
| | | 0010001 | 11h 4.7 | 0111010 | 3Ah 8.8 | 1100011 | 63h 12.9 |
| | | 0010010 | 12h 4.8 | 0111011 | 3Bh 8.9 | 1100100 | 64h 13 |
| | | 0010011 | 13h 4.9 | 0111100 | 3Ch 9 | 1100101 | 65h 13.1 |
| | | 0010100 | 14h 5 | 0111101 | 3Dh 9.1 | 1100110 | 66h 13.2 |
| | | 0010101 | 15h 5.1 | 0111110 | 3Eh 9.2 | 1100111 | 67h 13.3 |
| | | 0010110 | 16h 5.2 | 0111111 | 3Fh 9.3 | 1101000 | 68h 13.4 |
| | | 0010111 | 17h 5.3 | 1000000 | 40h 9.4 | 1101001 | 69h 13.5 |
| | | 0011000 | 18h 5.4 | 1000001 | 41h 9.5 | 1101010 | 6Ah 13.6 |
| | | 0011001 | 19h 5.5 | 1000010 | 42h 9.6 | 1101011 | 6Bh 13.7 |
| | | 0011010 | 1Ah 5.6 | 1000011 | 43h 9.7 | 1101100 | 6Ch 13.8 |
| | | 0011011 | 1Bh 5.7 | 1000100 | 44h 9.8 | 1101101 | 6Dh 13.9 |
| | | 0011100 | 1Ch 5.8 | 1000101 | 45h 9.9 | 1101110 | 6Eh 14 |
| | | 0011101 | 1Dh 5.9 | 1000110 | 46h 10 | 1101111 | 6Fh 14.1 |
| | | 0011110 | 1Eh 6 | 1000111 | 47h 10.1 | 1110000 | 70h 14.2 |
| | | 0011111 | 1Fh 6.1 | 1001000 | 48h 10.2 | 1110001 | 71h 14.3 |
| | | 0100000 | 20h 6.2 | 1001001 | 49h 10.3 | 1110010 | 72h 14.4 |
| | | 0100001 | 21h 6.3 | 1001010 | 4Ah 10.4 | 1110011 | 73h 14.5 |
| | | 0100010 | 22h 6.4 | 1001011 | 4Bh 10.5 | 1110100 | 74h 14.6 |
| | | 0100011 | 23h 6.5 | 1001100 | 4Ch 10.6 | 1110101 | 75h 14.7 |
| | | 0100100 | 24h 6.6 | 1001101 | 4Dh 10.7 | 1110110 | 76h 14.8 |
| | | 0100101 | 25h 6.7 | 1001110 | 4Eh 10.8 | 1110111 | 77h 14.9 |
| | | 0100110 | 26h 6.8 | 1001111 | 4Fh 10.9 | 1111000 | 78h 15 |
| | | 0100111 | 27h 6.9 | 1010000 | 50h 11 | other | 15 |
| | | 0101000 | 28h 7 | 1010001 | 51h 11.1 | | |

6-0
VSP_1 & VSPL_0 & VSPL_1

5th Parameter: Internal VSN_1 power selection

| Bit | Name | Description | | | | | | | | |
|---------|-------|-------------------------------|------------|-----------|------------|-----------|------------|---------|-----|-------|
| 6-0 | VSN_1 | Internal VSN power selection. | | | | | | | | |
| | | bit[6:0] | Voltage(V) | bit [6:0] | Voltage(V) | bit [6:0] | Voltage(V) | | | |
| | | 0000000 | 00h | -3 | 0101001 | 29h | -7.1 | 1010010 | 52h | -11.2 |
| | | 0000001 | 01h | -3.1 | 0101010 | 2Ah | -7.2 | 1010011 | 53h | -11.3 |
| | | 0000010 | 02h | -3.2 | 0101011 | 2Bh | -7.3 | 1010100 | 54h | -11.4 |
| | | 0000011 | 03h | -3.3 | 0101100 | 2Ch | -7.4 | 1010101 | 55h | -11.5 |
| | | 0000100 | 04h | -3.4 | 0101101 | 2Dh | -7.5 | 1010110 | 56h | -11.6 |
| | | 0000101 | 05h | -3.5 | 0101110 | 2Eh | -7.6 | 1010111 | 57h | -11.7 |
| | | 0000110 | 06h | -3.6 | 0101111 | 2Fh | -7.7 | 1011000 | 58h | -11.8 |
| | | 0000111 | 07h | -3.7 | 0110000 | 30h | -7.8 | 1011001 | 59h | -11.9 |
| | | 0001000 | 08h | -3.8 | 0110001 | 31h | -7.9 | 1011010 | 5Ah | -12 |
| | | 0001001 | 09h | -3.9 | 0110010 | 32h | -8 | 1011011 | 5Bh | -12.1 |
| | | 0001010 | 0Ah | -4 | 0110011 | 33h | -8.1 | 1011100 | 5Ch | -12.2 |
| | | 0001011 | 0Bh | -4.1 | 0110100 | 34h | -8.2 | 1011101 | 5Dh | -12.3 |
| | | 0001100 | 0Ch | -4.2 | 0110101 | 35h | -8.3 | 1011110 | 5Eh | -12.4 |
| | | 0001101 | 0Dh | -4.3 | 0110110 | 36h | -8.4 | 1011111 | 5Fh | -12.5 |
| | | 0001110 | 0Eh | -4.4 | 0110111 | 37h | -8.5 | 1100000 | 60h | -12.6 |
| | | 0001111 | 0Fh | -4.5 | 0111000 | 38h | -8.6 | 1100001 | 61h | -12.7 |
| | | 0010000 | 10h | -4.6 | 0111001 | 39h | -8.7 | 1100010 | 62h | -12.8 |
| | | 0010001 | 11h | -4.7 | 0111010 | 3Ah | -8.8 | 1100011 | 63h | -12.9 |
| | | 0010010 | 12h | -4.8 | 0111011 | 3Bh | -8.9 | 1100100 | 64h | -13 |
| | | 0010011 | 13h | -4.9 | 0111100 | 3Ch | -9 | 1100101 | 65h | -13.1 |
| | | 0010100 | 14h | -5 | 0111101 | 3Dh | -9.1 | 1100110 | 66h | -13.2 |
| | | 0010101 | 15h | -5.1 | 0111110 | 3Eh | -9.2 | 1100111 | 67h | -13.3 |
| | | 0010110 | 16h | -5.2 | 0111111 | 3Fh | -9.3 | 1101000 | 68h | -13.4 |
| | | 0010111 | 17h | -5.3 | 1000000 | 40h | -9.4 | 1101001 | 69h | -13.5 |
| | | 0011000 | 18h | -5.4 | 1000001 | 41h | -9.5 | 1101010 | 6Ah | -13.6 |
| | | 0011001 | 19h | -5.5 | 1000010 | 42h | -9.6 | 1101011 | 6Bh | -13.7 |
| | | 0011010 | 1Ah | -5.6 | 1000011 | 43h | -9.7 | 1101100 | 6Ch | -13.8 |
| | | 0011011 | 1Bh | -5.7 | 1000100 | 44h | -9.8 | 1101101 | 6Dh | -13.9 |
| 0011100 | 1Ch | -5.8 | 1000101 | 45h | -9.9 | 1101110 | 6Eh | -14 | | |
| 0011101 | 1Dh | -5.9 | 1000110 | 46h | -10 | 1101111 | 6Fh | -14.1 | | |
| 0011110 | 1Eh | -6 | 1000111 | 47h | -10.1 | 1110000 | 70h | -14.2 | | |
| 0011111 | 1Fh | -6.1 | 1001000 | 48h | -10.2 | 1110001 | 71h | -14.3 | | |
| 0100000 | 20h | -6.2 | 1001001 | 49h | -10.3 | 1110010 | 72h | -14.4 | | |
| 0100001 | 21h | -6.3 | 1001010 | 4Ah | -10.4 | 1110011 | 73h | -14.5 | | |
| 0100010 | 22h | -6.4 | 1001011 | 4Bh | -10.5 | 1110100 | 74h | -14.6 | | |
| 0100011 | 23h | -6.5 | 1001100 | 4Ch | -10.6 | 1110101 | 75h | -14.7 | | |
| 0100100 | 24h | -6.6 | 1001101 | 4Dh | -10.7 | 1110110 | 76h | -14.8 | | |
| 0100101 | 25h | -6.7 | 1001110 | 4Eh | -10.8 | 1110111 | 77h | -14.9 | | |
| 0100110 | 26h | -6.8 | 1001111 | 4Fh | -10.9 | 1111000 | 78h | -15 | | |
| 0100111 | 27h | -6.9 | 1010000 | 50h | -11 | other | | -15 | | |
| 0101000 | 28h | -7 | 1010001 | 51h | -7.1 | | | | | |

Notes:

1. VSP_0/VSN_0 voltage output is ±15 V fixed value.
2. When switching Mode0 or Mode1, the voltage output is:
 Mode0: VSP_0(+15) / VSN_0 (-15) / VSPL_0 (+3~+15)
 Mode1: VSP_1(+3 ~ +15) / VSN_1(-3 ~ -15) / VSPL_1(+3 ~ +15)

| | Mode0 | Mode1 |
|------|----------------|----------------|
| VSP | VSP_0(+15) | VSP_1(+3~+15) |
| VSN | VSN_0(-15) | VSN_1(-3~-15) |
| VSPL | VSPL_0(+3~+15) | VSPL_1(+3~+15) |

3. If gate voltage is set to +/-15v, +/-10v, IC will auto correct source voltage as follows
 I. VGP- VSP_0 / VSPL_0 / VSP_1 / VSPL_1 >= 2v
 II. VGN- VSN_0 / VSN_1 >= -2v
 For example:

| | symbol | Voltage setting | Real Voltage |
|---------|--------|-----------------|--------------|
| Voltage | VGP | 10v | +10v |
| | VGN | 10v | -10v |
| | VSP_0 | +15v | +8v |
| | VSN_0 | -15v | -8v |
| | VSP_1 | +5v | +5v |
| | VSN_1 | -5v | -5v |
| | VSPL | +15v | +8v |
| | VCOMH | +15v+(-2v) | +8v +(-2v) |
| | VCOML | -15v+(-2v) | -8v +(-2v) |
| | VCOMDC | -2v | -2v |

4. Voltage setting limit: VSP_0 ≥ VSPL_0 , VSP_1 ≥ VSPL_1

Restriction

| R02H | Bit | | | | | | | | | | |
|---------------------------|-----|------|----|----|----|----|----|----|----|----|------|
| Inst/Para | R/W | D/CX | D7 | D6 | D5 | D4 | D3 | D2 | D1 | D0 | Code |
| POF | W | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 0 | 02H |
| 1 st Parameter | W | 1 | - | - | - | - | - | - | - | - | 00 |

NOTE: "-" Don't care, can be set to VDD or GND level

| | |
|-------------|---|
| Description | -The command defines as : R02h = 0x00h <ul style="list-style-type: none"> After power off command, driver will power off base on power off sequence. After power off command, BUSY_N signal will drop from high to low. When finish the power off sequence, BUSY_N signal will rise from low to high. Power off command will turn off charge pump, T-con, source driver, gate driver, VCOM, temperature sensor, but register and SRAM data will keep until VDD off. SD output and VCOM will base on previous condition. It may have two conditions: 0v or floating. |
| Restriction | This command only active when BUSY_N = "1". |

| R04H | Bit | | | | | | | | | | |
|-----------|-----|------|----|----|----|----|----|----|----|----|------|
| Inst/Para | R/W | D/CX | D7 | D6 | D5 | D4 | D3 | D2 | D1 | D0 | Code |
| PON | W | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 04H |

NOTE: "-" Don't care, can be set to VDD or GND level

| | |
|-------------|--|
| Description | -The command defines as : <ul style="list-style-type: none"> After power on command, driver will power on base on power on sequence. After power on command, BUSY_N signal will drop from high to low. When finishing the power on sequence(base on PWR command), BUSY_N signal will rise from low to high. |
| Restriction | This command only active when BUSY_N = "1". |

| R06H | Bit | | | | | | | | | | |
|---------------------------|-----|------|----|----|---------------|----|---------------|----|---------------|----|------|
| Inst/Para | R/W | D/CX | D7 | D6 | D5 | D4 | D3 | D2 | D1 | D0 | Code |
| BTST | W | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 1 | 0 | 06H |
| 1 st Parameter | W | 1 | - | - | - | - | PHB_SFT [1:0] | | PHA_SFT [1:0] | | 00h |
| 2 nd Parameter | W | 1 | - | - | PHA_ON [5:0] | | | | | | 02h |
| 3 rd Parameter | W | 1 | - | - | PHA_OFF [5:0] | | | | | | 07h |
| 4 th Parameter | W | 1 | - | - | PHB_ON [5:0] | | | | | | 02h |
| 5 th Parameter | W | 1 | - | - | PHB_OFF [5:0] | | | | | | 07h |
| 6 th Parameter | W | 1 | - | - | PHC_ON [5:0] | | | | | | 02h |
| 7 th Parameter | W | 1 | - | - | PHC_OFF [5:0] | | | | | | 07h |

-The command define as follows:

1st Parameter:

| Bit | Name | Description |
|-----|---------|---|
| 1-0 | PHA_SFT | Soft start period of phase A: 00: 10mS (default) 01: 20mS 10: 30mS 11: 40mS |
| 3-2 | PHB_SFT | Soft start period of phase B: 00: 10mS (default) 01: 20mS 10: 30mS 11: 40mS |

Description

| Bit[5:0] | Description | Bit[5:0] | Description | Bit[5:0] | Description |
|----------|-------------|----------|-------------|----------|-------------|
| 000000 | strength1 | 010110 | strength23 | 101100 | strength45 |
| 000001 | strength2 | 010111 | strength24 | 101101 | strength46 |
| 000010 | strength3 | 011000 | strength25 | 101110 | strength47 |
| 000011 | strength4 | 011001 | strength26 | 101111 | strength48 |
| 000100 | strength5 | 011010 | strength27 | 110000 | strength49 |
| 000101 | strength6 | 011011 | strength28 | 110001 | strength50 |
| 000110 | strength7 | 011100 | strength29 | 110010 | strength51 |
| 000111 | strength8 | 011101 | strength30 | 110011 | strength52 |
| 001000 | strength9 | 011110 | strength31 | 110100 | strength53 |
| 001001 | strength10 | 011111 | strength32 | 110101 | strength54 |
| 001010 | strength11 | 100000 | strength33 | 110110 | strength55 |
| 001011 | strength12 | 100001 | strength34 | 110111 | strength56 |
| 001100 | strength13 | 100010 | strength35 | 111000 | strength57 |
| 001101 | strength14 | 100011 | strength36 | 111001 | strength58 |
| 001110 | strength15 | 100100 | strength37 | 111010 | strength59 |
| 001111 | strength16 | 100101 | strength38 | 111011 | strength60 |
| 010000 | strength17 | 100110 | strength39 | 111100 | strength61 |
| 010001 | strength18 | 100111 | strength40 | 111101 | strength62 |
| 010010 | strength19 | 101000 | strength41 | 111110 | strength63 |
| 010011 | strength20 | 101001 | strength42 | 111111 | strength64 |
| 010100 | strength21 | 101010 | strength43 | | |
| 010101 | strength22 | 101011 | strength44 | | |

Driving strength of PHA_ON & PHB_ON & PHC_ON

| Description | Bit[5:0] | | Description | Bit[5:0] | | Description | Bit[5:0] | | Description |
|---|----------|--|-------------|----------|--|-------------|----------|--|-------------|
| | | | | | | | | | |
| Minimum OFF time setting of PHA_OFF & PHB_OFF & PHC_OFF | 000000 | | Period1 | 010110 | | Period23 | 101100 | | Period45 |
| | 000001 | | Period2 | 010111 | | Period24 | 101101 | | Period46 |
| | 000010 | | Period3 | 011000 | | Period25 | 101110 | | Period47 |
| | 000011 | | Period4 | 011001 | | Period26 | 101111 | | Period48 |
| | 000100 | | Period5 | 011010 | | Period27 | 110000 | | Period49 |
| | 000101 | | Period6 | 011011 | | Period28 | 110001 | | Period50 |
| | 000110 | | Period7 | 011100 | | Period29 | 110010 | | Period51 |
| | 000111 | | Period8 | 011101 | | Period30 | 110011 | | Period52 |
| | 001000 | | Period9 | 011110 | | Period31 | 110100 | | Period53 |
| | 001001 | | Period10 | 011111 | | Period32 | 110101 | | Period54 |
| | 001010 | | Period11 | 100000 | | Period33 | 110110 | | Period55 |
| | 001011 | | Period12 | 100001 | | Period34 | 110111 | | Period56 |
| | 001100 | | Period13 | 100010 | | Period35 | 111000 | | Period57 |
| | 001101 | | Period14 | 100011 | | Period36 | 111001 | | Period58 |
| | 001110 | | Period15 | 100100 | | Period37 | 111010 | | Period59 |
| | 001111 | | Period16 | 100101 | | Period38 | 111011 | | Period60 |
| | 010000 | | Period17 | 100110 | | Period39 | 111100 | | Period61 |
| | 010001 | | Period18 | 100111 | | Period40 | 111101 | | Period62 |
| | 010010 | | Period19 | 101000 | | Period41 | 111110 | | Period63 |
| | 010011 | | Period20 | 101001 | | Period42 | 111111 | | Period64 |
| | 010100 | | Period21 | 101010 | | Period43 | | | |
| | 010101 | | Period22 | 101011 | | Period44 | | | |
| Restriction | | | | | | | | | |

| R07H | Bit | | | | | | | | | | |
|---------------------------|-----|------|----|----|----|----|----|----|----|----|------|
| Inst/Para | R/W | D/CX | D7 | D6 | D5 | D4 | D3 | D2 | D1 | D0 | Code |
| DSLTP | W | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 1 | 1 | 07H |
| 1 st Parameter | W | 1 | 1 | 0 | 1 | 0 | 0 | 1 | 0 | 1 | A5h |

NOTE: "-" Don't care, can be set to VDD or GND level

| | |
|-------------|--|
| Description | The command define as follows: After this command is transmitted, the chip would enter the deep-sleep mode to save power. The deep sleep mode would return to standby by hardware reset. The only one parameter is a check code, the command would be excited if check code = 0xA5. |
| Restriction | This command only active when BUSY_N = "1". |

| R10H | Bit | | | | | | | | | | |
|---------------------------|-----|------|------------|------------|------------|----------|----|----|----|----|------|
| Inst/Para | R/W | D/CX | D7 | D6 | D5 | D4 | D3 | D2 | D1 | D0 | Code |
| DTM | W | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 10H |
| 2 bit mode | W | 1 | | | | | | | | | |
| 1 st Parameter | W | 1 | Pixel1 | Pixel2 | Pixel3 | Pixel4 | | | | | 00h |
| ⋮ | W | 1 | ⋮ | ⋮ | ⋮ | ⋮ | | | | | 00h |
| M th Parameter | W | 1 | Pixel(n-3) | Pixel(n-2) | Pixel(n-1) | Pixel(n) | | | | | 00h |

NOTE: "-" Don't care, can be set to VDD or GND level

| | | | | |
|-------------|---|-------------------|----------------------|---|
| Description | The command define as follows: The register is indicates that user start to transmit data, then write to SRAM. While data transmission complete, user must send command 12H. Then chip will start to send data/VCOM for panel. | | | |
| | Pixel [1~n][1:0]: 2-bit/pixel | | | |
| | Image Data | DDX=1(default) | | DDX=0 |
| | Pixel[1:0] | Gray level select | IP output LUT select | Gray level select IP output LUT select |
| | 00b | Gray0 | ogray00 | Gray3 ogray03 |
| | 01b | Gray1 | ogray01 | Gray2 ogray02 |
| | 10b | Gray2 | ogray02 | Gray1 ogray01 |
| | 11b | Gray3 | ogray03 | Gray0 ogray00 |
| | <p>Data mapping example:</p> <p>When DDX=1, Pixel[1:0]=01 -> Gray level select=Gray1, follow LUT data output from IP output port"ogray01".</p> <p>When DDX=0, Pixel[1:0]=11 -> Gray level select=Gray0, follow LUT data output from IP output port"ogray00"</p> | | | |
| Restriction | | | | |

| R11H | Bit | | | | | | | | | | |
|---------------|-----|------|-----------|----|----|----|----|----|----|----|------|
| Inst/Para | R/W | D/CX | D7 | D6 | D5 | D4 | D3 | D2 | D1 | D0 | Code |
| DSP | W | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 1 | 11H |
| 1st Parameter | R | 1 | Data_flag | - | - | - | - | - | - | - | - |

NOTE: "-" Don't care, can be set to VDD or GND level

| | | | | | | | | | | | |
|-------------|--|-----------|---|--|--|--|--|--|--|--|--|
| Description | -The command defines as : ■While finished the data transmitting, user must send this command to driver and read Data_flag information. | | | | | | | | | | |
| | 1st Parameter: | | | | | | | | | | |
| | Bit | Name | Description | | | | | | | | |
| | 7 | Data_flag | 0: Driver didn't receive all the data. 1: Driver has already received all of the one frame data. | | | | | | | | |
| | After "Data Start" (10h) or "Data Stop" (11h) commands and when data_flag=1, BUSY_N signal will become "0" and the refreshing of panel starts. | | | | | | | | | | |
| Restriction | This command only actives when BUSY_N = "1". | | | | | | | | | | |

| R12H | Bit | | | | | | | | | | |
|---------------|-----|------|----|----|----|----|----|----|----|----|------|
| Inst/Para | R/W | D/CX | D7 | D6 | D5 | D4 | D3 | D2 | D1 | D0 | Code |
| DRF | W | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 1 | 0 | 12H |
| 1st Parameter | W | 1 | - | - | - | - | - | - | - | - | 00h |

NOTE: "-" Don't care, can be set to VDD or GND level

| | | | | | | | | | | | |
|-------------|---|--|--|--|--|--|--|--|--|--|--|
| Description | -The command defines as : | | | | | | | | | | |
| | <p>R12H=0x00</p> <p>While users send this command, driver will refresh display (data/VCOM) base on SRAM data and LUT.</p> <p>After display refresh command, BUSY_N signal will become "0"</p> | | | | | | | | | | |
| Restriction | This command only actives when BUSY_N = "1" | | | | | | | | | | |

| R17H | Bit | | | | | | | | | | |
|---------------------------|-----|------|---------|---------|---------|---------|---------|---------|---------|---------|------|
| Inst/Para | R/W | D/CX | D7 | D6 | D5 | D4 | D3 | D2 | D1 | D0 | Code |
| Auto Sequence | W | 0 | 0 | 0 | 0 | 1 | 0 | 1 | 1 | 1 | 17H |
| 1 st Parameter | W | 1 | Code[7] | Code[6] | Code[5] | Code[4] | Code[3] | Code[2] | Code[1] | Code[0] | A5h |

| | |
|-------------|---|
| Description | <p>The command can enable the internal sequence to execute several commands continuously. The successive execution can minimize idle time to avoid unnecessary power consumption and reduce the complexity of host's control procedure. The sequence contains several operations, including PON, DRF, POF, DSLP.</p> <p>AUTO (0x17) + Code(0xA5) = (PON→DRF→POF) AUTO (0x17) + Code(0xA7) = (PON→DRF→POF→DSLP)</p> |
| Restriction | This command only actives when BUSY_N = "1". |

| R30H | Bit | | | | | | | | | | |
|---------------------------|-----|------|----|----|----|----|------|-------|-------|-------|------|
| Inst/Para | R/W | D/CX | D7 | D6 | D5 | D4 | D3 | D2 | D1 | D0 | Code |
| PLL | W | 0 | 0 | 0 | 1 | 1 | 0 | 0 | 0 | 0 | 30H |
| 1 st Parameter | W | 1 | - | - | - | - | Dyna | FR[2] | FR[1] | FR[0] | 02h |

NOTE: "-" Don't care, can be set to VDD or GND level

| Description | <p>-The command defines as:</p> <p>The command controls the PLL clock frequency. The PLL structure must support the following frame rates:</p> <table border="1" style="margin-left: auto; margin-right: auto;"> <thead> <tr> <th>bit3</th> <th>Dynamic frame rate</th> </tr> </thead> <tbody> <tr> <td>0</td> <td>Disable(default)</td> </tr> <tr> <td>1</td> <td>Enable</td> </tr> </tbody> </table> <table border="1" style="margin-left: auto; margin-right: auto;"> <thead> <tr> <th>FR[2:0]</th> <th>Frame rate</th> </tr> </thead> <tbody> <tr> <td>000</td> <td>12.5 Hz</td> </tr> <tr> <td>001</td> <td>25 Hz</td> </tr> <tr> <td>010</td> <td>50 Hz(default)</td> </tr> <tr> <td>011</td> <td>65 Hz</td> </tr> <tr> <td>100</td> <td>75 Hz</td> </tr> <tr> <td>101</td> <td>85 Hz</td> </tr> <tr> <td>110</td> <td>100 Hz</td> </tr> <tr> <td>111</td> <td>120 Hz</td> </tr> </tbody> </table> | bit3 | Dynamic frame rate | 0 | Disable(default) | 1 | Enable | FR[2:0] | Frame rate | 000 | 12.5 Hz | 001 | 25 Hz | 010 | 50 Hz(default) | 011 | 65 Hz | 100 | 75 Hz | 101 | 85 Hz | 110 | 100 Hz | 111 | 120 Hz |
|-------------|---|------|--------------------|---|------------------|---|--------|---------|------------|-----|---------|-----|-------|-----|----------------|-----|-------|-----|-------|-----|-------|-----|--------|-----|--------|
| bit3 | Dynamic frame rate | | | | | | | | | | | | | | | | | | | | | | | | |
| 0 | Disable(default) | | | | | | | | | | | | | | | | | | | | | | | | |
| 1 | Enable | | | | | | | | | | | | | | | | | | | | | | | | |
| FR[2:0] | Frame rate | | | | | | | | | | | | | | | | | | | | | | | | |
| 000 | 12.5 Hz | | | | | | | | | | | | | | | | | | | | | | | | |
| 001 | 25 Hz | | | | | | | | | | | | | | | | | | | | | | | | |
| 010 | 50 Hz(default) | | | | | | | | | | | | | | | | | | | | | | | | |
| 011 | 65 Hz | | | | | | | | | | | | | | | | | | | | | | | | |
| 100 | 75 Hz | | | | | | | | | | | | | | | | | | | | | | | | |
| 101 | 85 Hz | | | | | | | | | | | | | | | | | | | | | | | | |
| 110 | 100 Hz | | | | | | | | | | | | | | | | | | | | | | | | |
| 111 | 120 Hz | | | | | | | | | | | | | | | | | | | | | | | | |

| | |
|-------------|-------------------------------------|
| remark | <p>-Horizontal</p> <p>-Vertical</p> |
| Restriction | |

| R40H | Bit | | | | | | | | | | |
|---------------------------|-----|------|-----------|----------|----------|----------|----------|----------|----------|----------|------|
| Inst/Para | R/W | D/CX | D7 | D6 | D5 | D4 | D3 | D2 | D1 | D0 | Code |
| TSC | W | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 40H |
| 1 st Parameter | R | 1 | D10/TS[7] | D9/TS[6] | D8/TS[5] | D7/TS[4] | D6/TS[3] | D5/TS[2] | D4/TS[1] | D3/TS[0] | - |
| 2 nd Parameter | R | 1 | D2/TS[9] | D1/TS[8] | D0 | - | - | - | - | - | - |

NOTE: "-" Don't care, can be set to VDD or GND level

Description

-The command define as follows:
 This command indicates the temperature value.
 If R41H(TSE) bit7 set to 0, this command reads internal temperature sensor value.
 If R41H(TSE) bit7 set to 1, this command reads external (LM75) temperature sensor value

| TS[7:0]/D[10:3] | T (°C) | TS[7:0]/D[10:3] | T (°C) | TS[7:0]/D[10:3] | T (°C) |
|-----------------|--------|-----------------|--------|-----------------|--------|
| 11100111 | -25 | 00000000 | 0 | 00011001 | 25 |
| 11101000 | -24 | 00000001 | 1 | 00011010 | 26 |
| 11101001 | -23 | 00000010 | 2 | 00011011 | 27 |
| 11101010 | -22 | 00000011 | 3 | 00011100 | 28 |
| 11101011 | -21 | 00000100 | 4 | 00011101 | 29 |
| 11101100 | -20 | 00000101 | 5 | 00011110 | 30 |
| 11101101 | -19 | 00000110 | 6 | 00011111 | 31 |
| 11101110 | -18 | 00000111 | 7 | 00100000 | 32 |
| 11101111 | -17 | 00001000 | 8 | 00100001 | 33 |
| 11110000 | -16 | 00001001 | 9 | 00100010 | 34 |
| 11110001 | -15 | 00001010 | 10 | 00100011 | 35 |
| 11110010 | -14 | 00001011 | 11 | 00100100 | 36 |
| 11110011 | -13 | 00001100 | 12 | 00100101 | 37 |
| 11110100 | -12 | 00001101 | 13 | 00100110 | 38 |
| 11110101 | -11 | 00001110 | 14 | 00100111 | 39 |
| 11110110 | -10 | 00001111 | 15 | 00101000 | 40 |
| 11110111 | -9 | 00010000 | 16 | 00101001 | 41 |
| 11111000 | -8 | 00010001 | 17 | 00101010 | 42 |
| 11111001 | -7 | 00010010 | 18 | 00101011 | 43 |
| 11111010 | -6 | 00010011 | 19 | 00101100 | 44 |
| 11111011 | -5 | 00010100 | 20 | 00101101 | 45 |
| 11111100 | -4 | 00010101 | 21 | 00101110 | 46 |
| 11111101 | -3 | 00010110 | 22 | 00101111 | 47 |
| 11111110 | -2 | 00010111 | 23 | 00110000 | 48 |
| 11111111 | -1 | 00011000 | 24 | 00110001 | 49 |

| TS[9:8] | T (°C) |
|---------|--------|
| 00 | +0 |
| 01 | +0.25 |
| 10 | +0.5 |
| 11 | +0.75 |

Restriction This command only actives when BUSY_N = "1".

| R41H | Bit | | | | | | | | | | |
|---------------------------|-----|------|-----|----|----|-------|-------|-------|-------|-------|------|
| Inst/Para | R/W | D/CX | D7 | D6 | D5 | D4 | D3 | D2 | D1 | D0 | Code |
| TSE | W | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 1 | 41H |
| 1 st Parameter | W | 1 | TSE | - | - | TO[4] | TO[3] | TO[2] | TO[1] | TO[0] | 00h |

NOTE: "-" Don't care, can be set to VDD or GND level

Description

-The command defines as:
 This command indicates the driver IC temperature sensor enable and calibration function.

Reserve one temperature offset TO[3:0] for calibration

- TO[3]: mean '+' or '-', while 0 is '+' ; 1 is '-'
- TO[2:0]: mean temperature offset value

| Bit | Name | Description |
|-------------|---|---|
| 3-0 | TO[3:0] | Temperature level: 0000: +0°C (default) 0001: +0.5°C 0010: +1°C 0011: +1.5°C 0100: +2°C 0101: +2.5°C 0110: +3°C 0111: +3.5°C 1000: -4°C 1001: -3.5°C 1010: -3°C 1011: -2.5°C 1100: -2°C 1101: -1.5°C 1110: -1°C 1111: -0.5°C |
| 4 | TO[4] | 0: +0.0°C (default) 1: +0.25°C |
| 7 | TSE | Internal temperature sensor enable 0: Internal temperature sensor enable.(default) 1: Internal temperature sensor disable, using external temperature sensor. |
| Restriction | This command only actives after R04H(PON) | |

| R42H | Bit | | | | | | | | | | |
|---------------------------|-----|------|----------|----------|----------|----------|----------|----------|----------|----------|------|
| Inst/Para | R/W | D/CX | D7 | D6 | D5 | D4 | D3 | D2 | D1 | D0 | Code |
| TSW | W | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 1 | 0 | 42H |
| 1 st Parameter | W | 1 | WATTR[7] | WATTR[6] | WATTR[5] | WATTR[4] | WATTR[3] | WATTR[2] | WATTR[1] | WATTR[0] | 00h |
| 2 nd Parameter | W | 1 | WMSB[7] | WMSB[6] | WMSB[5] | WMSB[4] | WMSB[3] | WMSB[2] | WMSB[1] | WMSB[0] | 00h |
| 3 rd Parameter | W | 1 | WLSB[7] | WLSB[6] | WLSB[5] | WLSB[4] | WLSB[3] | WLSB[2] | WLSB[1] | WLSB[0] | 00h |

NOTE: "-" Don't care, can be set to VDD or GND level

| Description | -The command defines as: This command writes the temperature. 1 st Parameter: <table border="1"> <thead> <tr> <th>Bit</th> <th>Name</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>2-0</td> <td>WATTR[2:0]</td> <td>Pointer setting</td> </tr> <tr> <td>5-3</td> <td>WATTR[5:3]</td> <td>User-defined address bits (A2, A1, A0)</td> </tr> <tr> <td>7-6</td> <td>WATTR[7:6]</td> <td> I2C Write Byte Number 00: 1 byte (head byte only) 01: 2 bytes (head byte + pointer) 10: 3 bytes (head byte + pointer + 1st parameter) 11: 4 bytes (head byte + pointer + 1st parameter + 2nd parameter) </td> </tr> </tbody> </table> 2 nd Parameter: <table border="1"> <thead> <tr> <th>Bit</th> <th>Name</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>7-0</td> <td>WMSB[7:0]</td> <td>MSByte of write-data to external temperature sensor</td> </tr> </tbody> </table> 3 rd Parameter: <table border="1"> <thead> <tr> <th>Bit</th> <th>Name</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>7-0</td> <td>WLSB[7:0]</td> <td>LSByte of write-data to external temperature sensor</td> </tr> </tbody> </table> | Bit | Name | Description | 2-0 | WATTR[2:0] | Pointer setting | 5-3 | WATTR[5:3] | User-defined address bits (A2, A1, A0) | 7-6 | WATTR[7:6] | I2C Write Byte Number 00: 1 byte (head byte only) 01: 2 bytes (head byte + pointer) 10: 3 bytes (head byte + pointer + 1st parameter) 11: 4 bytes (head byte + pointer + 1st parameter + 2nd parameter) | Bit | Name | Description | 7-0 | WMSB[7:0] | MSByte of write-data to external temperature sensor | Bit | Name | Description | 7-0 | WLSB[7:0] | LSByte of write-data to external temperature sensor |
|-------------|--|---|------|-------------|-----|------------|-----------------|-----|------------|--|-----|------------|---|-----|------|-------------|-----|-----------|---|-----|------|-------------|-----|-----------|---|
| Bit | Name | Description | | | | | | | | | | | | | | | | | | | | | | | |
| 2-0 | WATTR[2:0] | Pointer setting | | | | | | | | | | | | | | | | | | | | | | | |
| 5-3 | WATTR[5:3] | User-defined address bits (A2, A1, A0) | | | | | | | | | | | | | | | | | | | | | | | |
| 7-6 | WATTR[7:6] | I2C Write Byte Number 00: 1 byte (head byte only) 01: 2 bytes (head byte + pointer) 10: 3 bytes (head byte + pointer + 1st parameter) 11: 4 bytes (head byte + pointer + 1st parameter + 2nd parameter) | | | | | | | | | | | | | | | | | | | | | | | |
| Bit | Name | Description | | | | | | | | | | | | | | | | | | | | | | | |
| 7-0 | WMSB[7:0] | MSByte of write-data to external temperature sensor | | | | | | | | | | | | | | | | | | | | | | | |
| Bit | Name | Description | | | | | | | | | | | | | | | | | | | | | | | |
| 7-0 | WLSB[7:0] | LSByte of write-data to external temperature sensor | | | | | | | | | | | | | | | | | | | | | | | |
| Restriction | This command only actives after R04H(PON) | | | | | | | | | | | | | | | | | | | | | | | | |

| R43H | Bit | | | | | | | | | | |
|---------------------------|-----|------|---------|---------|---------|---------|---------|---------|---------|---------|------|
| Inst/Para | R/W | D/CX | D7 | D6 | D5 | D4 | D3 | D2 | D1 | D0 | Code |
| TSR | W | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 1 | 1 | 43H |
| 1 st Parameter | R | 1 | RMSB[7] | RMSB[6] | RMSB[5] | RMSB[4] | RMSB[3] | RMSB[2] | RMSB[1] | RMSB[0] | - |
| 2 nd Parameter | R | 1 | RLSB[7] | RLSB[6] | RLSB[5] | RLSB[4] | RLSB[3] | RLSB[2] | RLSB[1] | RLSB[0] | - |


NOTE: "-" Don't care, can be set to VDD or GND level

| Description | <p>-The command defines as:</p> <p>This command reads the temperature sensed by the temperature sensor.</p> <p>1st Parameter:</p> <table border="1"> <thead> <tr> <th>Bit</th> <th>Name</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>7-0</td> <td>RMSB[7:0]</td> <td>MSByte of read-data from external temperature sensor</td> </tr> </tbody> </table> <p>2nd Parameter:</p> <table border="1"> <thead> <tr> <th>Bit</th> <th>Name</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>7-0</td> <td>RLSB[7:0]</td> <td>LSByte of write-data from external temperature sensor</td> </tr> </tbody> </table> | Bit | Name | Description | 7-0 | RMSB[7:0] | MSByte of read-data from external temperature sensor | Bit | Name | Description | 7-0 | RLSB[7:0] | LSByte of write-data from external temperature sensor |
|-------------|--|---|------|-------------|-----|-----------|--|-----|------|-------------|-----|-----------|---|
| Bit | Name | Description | | | | | | | | | | | |
| 7-0 | RMSB[7:0] | MSByte of read-data from external temperature sensor | | | | | | | | | | | |
| Bit | Name | Description | | | | | | | | | | | |
| 7-0 | RLSB[7:0] | LSByte of write-data from external temperature sensor | | | | | | | | | | | |
| Restriction | This command only actives after R04H(PON) | | | | | | | | | | | | |

| R50H | | Bit | | | | | | | | | |
|---------------------------|-----|------|--------|--------|--------|-----|--------|--------|--------|--------|------|
| Inst/Para | R/W | D/CX | D7 | D6 | D5 | D4 | D3 | D2 | D1 | D0 | Code |
| CDI | W | 0 | 0 | 1 | 0 | 1 | 0 | 0 | 0 | 0 | 50H |
| 1 st Parameter | W | 1 | VBD[2] | VBD[1] | VBD[0] | DDX | CDI[3] | CDI[2] | CDI[1] | CDI[0] | 97h |

NOTE: "-" Don't care, can be set to VDD or GND level

| Description | <p>-The command defines as:</p> <p>This command can set 2 kinds of parameters, 1.VCOM to data output interval(CDI)</p> <p>CDI[3:0]: This command indicates the interval of VCOM and data output. When setting the vertical back porch, the total blanking will be keep (55hsync).</p> <table border="1"> <thead> <tr> <th>Bit</th> <th>Name</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td rowspan="16">3-0</td> <td rowspan="16">CDI[3:0]</td> <td>Vcom and data interval</td> </tr> <tr><td>0000: 17 hsync</td></tr> <tr><td>0001: 16 hsync</td></tr> <tr><td>0010: 15 hsync</td></tr> <tr><td>0011: 14 hsync</td></tr> <tr><td>0100: 13 hsync</td></tr> <tr><td>0101: 12 hsync</td></tr> <tr><td>0110: 11 hsync</td></tr> <tr><td>0111: 10 hsync(default)</td></tr> <tr><td>1000: 9 hsync</td></tr> <tr><td>1001: 8 hsync</td></tr> <tr><td>1010: 7 hsync</td></tr> <tr><td>1011: 6 hsync</td></tr> <tr><td>1100: 5 hsync</td></tr> <tr><td>1101: 4 hsync</td></tr> <tr><td>1110: 3 hsync</td></tr> <tr><td>1111: 2 hsync</td></tr> </tbody> </table> | Bit | Name | Description | 3-0 | CDI[3:0] | Vcom and data interval | 0000: 17 hsync | 0001: 16 hsync | 0010: 15 hsync | 0011: 14 hsync | 0100: 13 hsync | 0101: 12 hsync | 0110: 11 hsync | 0111: 10 hsync(default) | 1000: 9 hsync | 1001: 8 hsync | 1010: 7 hsync | 1011: 6 hsync | 1100: 5 hsync | 1101: 4 hsync | 1110: 3 hsync | 1111: 2 hsync |
|---------------|--|-------------------------|------|-------------|-----|----------|------------------------|----------------|----------------|----------------|----------------|----------------|----------------|----------------|-------------------------|---------------|---------------|---------------|---------------|---------------|---------------|---------------|---------------|
| Bit | Name | Description | | | | | | | | | | | | | | | | | | | | | |
| 3-0 | CDI[3:0] | Vcom and data interval | | | | | | | | | | | | | | | | | | | | | |
| | | 0000: 17 hsync | | | | | | | | | | | | | | | | | | | | | |
| | | 0001: 16 hsync | | | | | | | | | | | | | | | | | | | | | |
| | | 0010: 15 hsync | | | | | | | | | | | | | | | | | | | | | |
| | | 0011: 14 hsync | | | | | | | | | | | | | | | | | | | | | |
| | | 0100: 13 hsync | | | | | | | | | | | | | | | | | | | | | |
| | | 0101: 12 hsync | | | | | | | | | | | | | | | | | | | | | |
| | | 0110: 11 hsync | | | | | | | | | | | | | | | | | | | | | |
| | | 0111: 10 hsync(default) | | | | | | | | | | | | | | | | | | | | | |
| | | 1000: 9 hsync | | | | | | | | | | | | | | | | | | | | | |
| | | 1001: 8 hsync | | | | | | | | | | | | | | | | | | | | | |
| | | 1010: 7 hsync | | | | | | | | | | | | | | | | | | | | | |
| | | 1011: 6 hsync | | | | | | | | | | | | | | | | | | | | | |
| | | 1100: 5 hsync | | | | | | | | | | | | | | | | | | | | | |
| | | 1101: 4 hsync | | | | | | | | | | | | | | | | | | | | | |
| | | 1110: 3 hsync | | | | | | | | | | | | | | | | | | | | | |
| 1111: 2 hsync | | | | | | | | | | | | | | | | | | | | | | | |



VBD[2:0]: Border data selection. (from LUT output by IP port border_w[1:0])

This register will make boarder pin output being mapped to a certain gray scale.

| Bit 4 | Bit7-5 | Description | IP setting for Border LUT select |
|-------------|----------|-------------|----------------------------------|
| DDX | VBD[2:0] | Gray level | |
| 0 | 000 | Floating | N/A |
| | 001 | Gray3 | border_buf=011 |
| | 010 | Gray2 | border_buf=010 |
| | 011 | Gray1 | border_buf=001 |
| | 100 | Gray0 | border_buf=000 |
| 1 (default) | 000 | Gray0 | border_buf=000 |
| | 001 | Gray1 | border_buf=001 |
| | 010 | Gray2 | border_buf=010 |
| | 011 | Gray3 | border_buf=011 |
| | 100 | Floating | N/A |

Border output voltage level: The level selection is based on mapping LUT data.

Ex: Gray 1 waveform is mapping to 15V, without VCOM offset, the real output on Boarder pin shall be 15V.

Boarder output will follow FOPT definition being defined in R00h.

| R51H | Bit | | | | | | | | | | |
|---------------------------|-----|------|----|----|----|----|----|----|----|-----|------|
| Inst/Para | R/W | D/CX | D7 | D6 | D5 | D4 | D3 | D2 | D1 | D0 | Code |
| LPD | W | 0 | 0 | 1 | 0 | 1 | 0 | 0 | 0 | 1 | 51H |
| 1 st Parameter | R | 1 | - | - | - | - | - | - | - | LPD | -- |

NOTE: "-" Don't care, can be set to VDD or GND level

Description

-The command defines as:
 This command indicates the input power condition. Host can read this data to understand the battery's condition.
 When LPD="1", system input power is normal.
 When LPD="0", system input power is lower (VDD<2.5v, which could be select in RE4H (LVSEL)).

1st Parameter:

| Bit 0 | LPD |
|-------|------------------|
| 0 | Low power input. |
| 1 | Normal status. |

Restriction

This command only actives when BUSY_N = "1".

| R61H | Bit | | | | | | | | | | |
|---------------------------|-----|------|---------|---------|---------|---------|---------|---------|---------|---------|------|
| Inst/Para | R/W | D/CX | D7 | D6 | D5 | D4 | D3 | D2 | D1 | D0 | Code |
| TRES | W | 0 | 0 | 1 | 1 | 0 | 0 | 0 | 0 | 1 | 61H |
| 1 st Parameter | W | 1 | - | - | - | - | - | - | HRES(9) | HRES(8) | 00h |
| 2 nd Parameter | W | 1 | HRES(7) | HRES(6) | HRES(5) | HRES(4) | HRES(3) | HRES(2) | 0 | 0 | 00h |
| 3 th Parameter | W | 1 | - | - | - | - | - | - | VRES(9) | VRES(8) | 00h |
| 4 th Parameter | W | 1 | VRES(7) | VRES(6) | VRES(5) | VRES(4) | VRES(3) | VRES(2) | VRES(1) | VRES(0) | 00h |

NOTE: "-" Don't care, can be set to VDD or GND level

| | |
|-------------|--|
| Description | <p>-The command define as follows: When using register: Horizontal display resolution(source) = HRES Vertical display resolution(gate) = VRES</p> <p>Note: No matter HRES[9:8],HRES[1:0],VRST[9] value being filled, it's always be 00b.</p> <p>Channel disable calculation: GD : First G active = G0; LAST active GD= first active +VRES[9:0] -1 SD : First active channel: =S0 ; LAST active SD= first active +HRES[9:2]*4-1</p> <p>EX :200X384 GD: First G active = G0 LAST active GD= 0+384-1= 383; (G383) SD : First active channel: =S0 LAST active SD=0+50*4-1=199; (S199)</p> <p>Note : Only supports source 200.ch for source 184ch. above</p> |
| Restriction | Horizontal resolution should be 4-multiple. |

| R65H | | Bit | | | | | | | | | |
|---------------------------|-----|------|------------|------------|------------|------------|------------|------------|------------|------------|------|
| Inst/Para | R/W | D/CX | D7 | D6 | D5 | D4 | D3 | D2 | D1 | D0 | Code |
| GSST | W | 0 | 0 | 1 | 1 | 0 | 0 | 1 | 0 | 1 | 65H |
| 1 st Parameter | W | 1 | - | - | - | - | - | - | S_start[9] | S_start[8] | 00h |
| 2 nd Parameter | W | 1 | S_start[7] | S_start[6] | S_start[5] | S_start[4] | S_start[3] | S_start[2] | 0 | 0 | 00h |
| 3 rd Parameter | W | 1 | - | - | - | - | - | - | G_start[9] | G_start[8] | 00h |
| 4 th Parameter | W | 1 | G_start[7] | G_start[6] | G_start[6] | G_start[4] | G_start[3] | G_start[2] | G_start[1] | G_start[0] | 00h |

NOTE: "-" Don't care, can be set to VDD or GND level

| | |
|-------------|---|
| Description | <p>-The command define as follows:</p> <p>Note: No matter S_start[9:8], S_start [1:0],VRST[9] value being filled, it's always be 00b.</p> <p>1.S_Start [7:0] describe which source output line is the first date line 2.G_Start[8:0] describe which gate line is the first scan line</p> |
| Restriction | S_Start should be the multiple of 4 |

| R70H | | Bit | | | | | | | | | |
|---------------------------|-----|------|----|----|----|----|----|----|----|----|------|
| Inst/Para | R/W | D/CX | D7 | D6 | D5 | D4 | D3 | D2 | D1 | D0 | Code |
| REV | W | 0 | 0 | 1 | 1 | 1 | 0 | 0 | 0 | 0 | 70H |
| 1 st Parameter | R | 1 | 1 | 0 | 0 | 0 | 0 | 0 | 1 | 1 | 85h |
| 2 nd Parameter | R | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 0 | 02h |
| 3 rd Parameter | R | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 01h |

NOTE: "-" Don't care, can be set to VDD or GND level

| Description | <p>-The command defines as:</p> <p>1st & 2nd & 3rd Parameter:</p> <table border="1"> <thead> <tr> <th>Bit</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>7-0</td> <td>CHIP_REV</td> </tr> </tbody> </table> | Bit | Description | 7-0 | CHIP_REV |
|-------------|---|-----|-------------|-----|----------|
| Bit | Description | | | | |
| 7-0 | CHIP_REV | | | | |
| Restriction | | | | | |

| R80H | Bit | | | | | | | | | | |
|---------------------------|-----|------|------|------|---------|---------|-----|------|-----|------|------|
| Inst/Para | R/W | D/CX | D7 | D6 | D5 | D4 | D3 | D2 | D1 | D0 | Code |
| AMV | W | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 80H |
| 1 st Parameter | W | 1 | P[1] | P[0] | AMVT[1] | AMVT[0] | XON | AMVS | AMV | AMVE | 00h |

NOTE: "-" Don't care, can be set to VDD or GND level

| | | | | | | | | | | | |
|---|--|---|-------------|--|--|--|--|--|--|--|--|
| Description | -The command defines as: This command indicates the IC status. Host can read this data to understand the IC status. 1 st Parameter: | | | | | | | | | | |
| | Bit | Name | Description | | | | | | | | |
| 0 | AMVE | AMVE: Auto Measure Vcom Setting 0: Auto measure VCOM disable (default) 1: Auto measure VCOM enable | | | | | | | | | |
| 1 | AMV | AMV: Analog signal 0: Get Vcom value from R81h(default) 1: Get Vcom value in analog signal | | | | | | | | | |
| 2 | AMVS | AMVS: setting for Source output of AMV 0: Source output 0V during Auto Measure VCOM period. (default) 1: Source output VSPL_0 during Auto Measure VCOM period. | | | | | | | | | |
| 3 | XON | XON: setting for all Gate ON of AMV 0: Gate normally scan during Auto Measure VCOM period. (default) 1: All Gate ON during Auto Measure VCOM period. | | | | | | | | | |
| 5-4 | AMVT[1:0] | The sensing time of VCOM detection 00: 5s (default) 01: 10s 10: 15s 11: 20s | | | | | | | | | |
| 7-6 | P[1:0] | The sensing points of sampling time 00: 2 (default) 01: 4 10: 8 11: 16 Sampling time = the last quarter of sensing time (T) VCOM = average of N points. N=2,4,8,16 | | | | | | | | | |
| <p>The diagram shows three signals: Source voltage (constant high), Vcom (low during sensing), and BUSY_N (low during sensing). A horizontal arrow indicates the 'Status of Vcom controlled by sensing mode'. A vertical double-headed arrow indicates 'The last quarter of sensing time'. Below the Vcom signal, it says 'Average of N point. N=2,4,8,16'.</p> | | | | | | | | | | | |
| Restriction | This command only activates when BUSY_N = "1". | | | | | | | | | | |

| R81H | Bit | | | | | | | | | | |
|---------------------------|-----|------|----|-------|-------|-------|-------|-------|-------|-------|------|
| Inst/Para | R/W | D/CX | D7 | D6 | D5 | D4 | D3 | D2 | D1 | D0 | Code |
| VV | W | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 81H |
| 1 st Parameter | R | 1 | - | VV[6] | VV[5] | VV[4] | VV[3] | VV[2] | VV[1] | VV[0] | - |

NOTE: "-" Don't care, can be set to VDD or GND level

| | | | | | | | | | | | |
|-------------|---|-------------|------------|-----------|------------|-----------|------------|-----------|------------|-----------|------------|
| Description | -The command defines as: This command could get the VCOM value | | | | | | | | | | |
| | 1 st Parameter: | | | | | | | | | | |
| 6-0 | VV[6:0] | Description | | | | | | | | | |
| | | VCOM value | | | | | | | | | |
| | | VCOM[6:0] | Voltage(V) | VCOM[6:0] | Voltage(V) | VCOM[6:0] | Voltage(V) | VCOM[6:0] | Voltage(V) | VCOM[6:0] | Voltage(V) |
| | | 0000000 | 00h | 0 | 0011100 | 1Ch | -1.4 | 0111000 | 38h | -2.8 | |
| | | 0000001 | 01h | -0.05 | 0011101 | 1Dh | -1.45 | 0111001 | 39h | -2.85 | |
| | | 0000010 | 02h | -0.1 | 0011110 | 1Eh | -1.5 | 0111010 | 3Ah | -2.9 | |
| | | 0000011 | 03h | -0.15 | 0011111 | 1Fh | -1.55 | 0111011 | 3Bh | -2.95 | |
| | | 0000100 | 04h | -0.2 | 0100000 | 20h | -1.6 | 0111100 | 3Ch | -3 | |
| | | 0000101 | 05h | -0.25 | 0100001 | 21h | -1.65 | 0111101 | 3Dh | -3.05 | |
| | | 0000110 | 06h | -0.3 | 0100010 | 22h | -1.7 | 0111110 | 3Eh | -3.1 | |
| | | 0000111 | 07h | -0.35 | 0100011 | 23h | -1.75 | 0111111 | 3Fh | -3.15 | |
| | | 0001000 | 08h | -0.4 | 0100100 | 24h | -1.8 | 1000000 | 40h | -3.2 | |
| | | 0001001 | 09h | -0.45 | 0100101 | 25h | -1.85 | 1000001 | 41h | -3.25 | |
| | | 0001010 | 0Ah | -0.5 | 0100110 | 26h | -1.9 | 1000010 | 42h | -3.3 | |
| | | 0001011 | 0Bh | -0.55 | 0100111 | 27h | -1.95 | 1000011 | 43h | -3.35 | |
| | | 0001100 | 0Ch | -0.6 | 0101000 | 28h | -2 | 1000100 | 44h | -3.4 | |
| | | 0001101 | 0Dh | -0.65 | 0101001 | 29h | -2.05 | 1000101 | 45h | -3.45 | |
| | | 0001110 | 0Eh | -0.7 | 0101010 | 2Ah | -2.1 | 1000110 | 46h | -3.5 | |
| | | 0001111 | 0Fh | -0.75 | 0101011 | 2Bh | -2.15 | 1000111 | 47h | -3.55 | |
| | | 0010000 | 10h | -0.8 | 0101100 | 2Ch | -2.2 | 1001000 | 48h | -3.6 | |
| | | 0010001 | 11h | -0.85 | 0101101 | 2Dh | -2.25 | 1001001 | 49h | -3.65 | |
| | | 0010010 | 12h | -0.9 | 0101110 | 2Eh | -2.3 | 1001010 | 4Ah | -3.7 | |
| | | 0010011 | 13h | -0.95 | 0101111 | 2Fh | -2.35 | 1001011 | 4Bh | -3.75 | |
| | | 0010100 | 14h | -1 | 0110000 | 30h | -2.4 | 1001100 | 4Ch | -3.8 | |
| | | 0010101 | 15h | -1.05 | 0110001 | 31h | -2.45 | 1001101 | 4Dh | -3.85 | |
| | | 0010110 | 16h | -1.1 | 0110010 | 32h | -2.5 | 1001110 | 4Eh | -3.9 | |
| | | 0010111 | 17h | -1.15 | 0110011 | 33h | -2.55 | 1001111 | 4Fh | -3.95 | |
| | | 0011000 | 18h | -1.2 | 0110100 | 34h | -2.6 | 1010000 | 50h | -4 | |
| | | 0011001 | 19h | -1.25 | 0110101 | 35h | -2.65 | other | | -4 | |
| | | 0011010 | 1Ah | -1.3 | 0110110 | 36h | -2.7 | | | | |
| | | 0011011 | 1Bh | -1.35 | 0110111 | 37h | -2.75 | | | | |
| Restriction | | | | | | | | | | | |

| R82H | Bit | | | | | | | | | | |
|---------------------------|-----|------|---------|---------|---------|----------|----------|----------|----------|----------|------|
| Inst/Para | R/W | D/CX | D7 | D6 | D5 | D4 | D3 | D2 | D1 | D0 | Code |
| VDCS | W | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 1 | 0 | 82H |
| 1 st Parameter | W | 1 | MTP_VCM | VDCS[6] | VDCS[5] | VDCS [4] | VDCS [3] | VDCS [2] | VDCS [1] | VDCS [0] | 00h |

NOTE: "-" Don't care, can be set to VDD or GND level

| | | | | | | | | | | | |
|-------------|--|-------------|------------|------------|------------|-----------|------------|-----------|------------|-----------|------------|
| Description | -The command defines as: This command set the VCOM DC value. Driver will base on this value for VCM_DC. | | | | | | | | | | |
| | 1 st Parameter: | | | | | | | | | | |
| | | Description | | | | | | | | | |
| | | VCOM value | | | | | | | | | |
| | | VCOM[6:0] | Voltage(V) | VCOM[6:0] | Voltage(V) | VCOM[6:0] | Voltage(V) | VCOM[6:0] | Voltage(V) | VCOM[6:0] | Voltage(V) |
| | | 0000000 | 00h | 0(default) | 0011100 | 1Ch | -1.4 | 0111000 | 38h | -2.8 | |
| | | 0000001 | 01h | -0.05 | 0011101 | 1Dh | -1.45 | 0111001 | 39h | -2.85 | |
| | | 0000010 | 02h | -0.1 | 0011110 | 1Eh | -1.5 | 0111010 | 3Ah | -2.9 | |

| | | | | | | | | | | |
|-----|-----------|---------|-----|-------|---------|-----|-------|---------|-----|-------|
| 6-0 | VDCS[6:0] | 0000011 | 03h | -0.15 | 0011111 | 1Fh | -1.55 | 0111011 | 3Bh | -2.95 |
| | | 0000100 | 04h | -0.2 | 0100000 | 20h | -1.6 | 0111100 | 3Ch | -3 |
| | | 0000101 | 05h | -0.25 | 0100001 | 21h | -1.65 | 0111101 | 3Dh | -3.05 |
| | | 0000110 | 06h | -0.3 | 0100010 | 22h | -1.7 | 0111110 | 3Eh | -3.1 |
| | | 0000111 | 07h | -0.35 | 0100011 | 23h | -1.75 | 0111111 | 3Fh | -3.15 |
| | | 0001000 | 08h | -0.4 | 0100100 | 24h | -1.8 | 1000000 | 40h | -3.2 |
| | | 0001001 | 09h | -0.45 | 0100101 | 25h | -1.85 | 1000001 | 41h | -3.25 |
| | | 0001010 | 0Ah | -0.5 | 0100110 | 26h | -1.9 | 1000010 | 42h | -3.3 |
| | | 0001011 | 0Bh | -0.55 | 0100111 | 27h | -1.95 | 1000011 | 43h | -3.35 |
| | | 0001100 | 0Ch | -0.6 | 0101000 | 28h | -2 | 1000100 | 44h | -3.4 |
| | | 0001101 | 0Dh | -0.65 | 0101001 | 29h | -2.05 | 1000101 | 45h | -3.45 |
| | | 0001110 | 0Eh | -0.7 | 0101010 | 2Ah | -2.1 | 1000110 | 46h | -3.5 |
| | | 0001111 | 0Fh | -0.75 | 0101011 | 2Bh | -2.15 | 1000111 | 47h | -3.55 |
| | | 0010000 | 10h | -0.8 | 0101100 | 2Ch | -2.2 | 1001000 | 48h | -3.6 |
| | | 0010001 | 11h | -0.85 | 0101101 | 2Dh | -2.25 | 1001001 | 49h | -3.65 |
| | | 0010010 | 12h | -0.9 | 0101110 | 2Eh | -2.3 | 1001010 | 4Ah | -3.7 |
| | | 0010011 | 13h | -0.95 | 0101111 | 2Fh | -2.35 | 1001011 | 4Bh | -3.75 |
| | | 0010100 | 14h | -1 | 0110000 | 30h | -2.4 | 1001100 | 4Ch | -3.8 |
| | | 0010101 | 15h | -1.05 | 0110001 | 31h | -2.45 | 1001101 | 4Dh | -3.85 |
| | | 0010110 | 16h | -1.1 | 0110010 | 32h | -2.5 | 1001110 | 4Eh | -3.9 |
| | | 0010111 | 17h | -1.15 | 0110011 | 33h | -2.55 | 1001111 | 4Fh | -3.95 |
| | | 0011000 | 18h | -1.2 | 0110100 | 34h | -2.6 | 1010000 | 50h | -4 |
| | | 0011001 | 19h | -1.25 | 0110101 | 35h | -2.65 | other | -4 | |
| | | 0011010 | 1Ah | -1.3 | 0110110 | 36h | -2.7 | | | |
| | | 0011011 | 1Bh | -1.35 | 0110111 | 37h | -2.75 | | | |

| | | |
|---|---------|--|
| 7 | MTP_VCM | Follow MTP VCOM value in MTP mode 0: From the setting of MTP (default) 1: From the setting of register |
|---|---------|--|

Restriction

| R83H | Bit | | | | | | | | | | |
|---------------------------|-----|------|---------|---------|---------|---------|---------|---------|---------|---------|------|
| Inst/Para | R/W | D/CX | D7 | D6 | D5 | D4 | D3 | D2 | D1 | D0 | Code |
| PTL | W | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 1 | 1 | 83H |
| 1 st Parameter | W | 1 | - | - | - | - | - | - | HRST[9] | HRST[8] | 00h |
| 2 nd Parameter | W | 1 | HRST[7] | HRST[6] | HRST[5] | HRST[4] | HRST[3] | HRST[2] | - | - | 00h |
| 3 rd Parameter | W | 1 | - | - | - | - | - | - | HRED[9] | HRED[8] | 00h |
| 4 th Parameter | W | 1 | HRED[7] | HRED[6] | HRED[5] | HRED[4] | HRED[3] | HRED[2] | - | - | 00h |
| 5 th Parameter | W | 1 | - | - | - | - | - | - | VRST[9] | VRST[8] | 00h |
| 6 th Parameter | W | 1 | VRST[7] | VRST[6] | VRST[5] | VRST[4] | VRST[3] | VRST[2] | VRST[1] | VRST[0] | 00h |
| 7 th Parameter | W | 1 | - | - | - | - | - | - | VRED[9] | VRED[8] | 00h |
| 8 th Parameter | W | 1 | VRED[7] | VRED[6] | VRED[5] | VRED[4] | VRED[3] | VRED[2] | VRED[1] | VRED[0] | 00h |
| 9 th Parameter | W | 1 | - | - | - | - | - | - | - | PMODE | 00h |

NOTE: "-" Don't care, can be set to VDD or GND level

| Description | -This command sets partial window. | | | | | | | | | | | | | | | | | | | | | |
|-------------|---|--|--|--|--|--|--|--|--|--|--|------|-------------|-----------|--------------------------|-----------|---|-----------|-------------------------|-----------|---|-------|
| | <table border="1"> <thead> <tr> <th>Name</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>HRST[9:2]</td> <td>Horizontal start address</td> </tr> <tr> <td>HRED[9:2]</td> <td>Horizontal end address. HRED must be greater than HRST.</td> </tr> <tr> <td>VRST[9:0]</td> <td>Vertical start address.</td> </tr> <tr> <td>VRED[9:0]</td> <td>Vertical end address. VRED must be greater than VRST.</td> </tr> <tr> <td>PMODE</td> <td>0: disable partial mode(default) 1: enable partial mode</td> </tr> </tbody> </table> <p>Note: No matter HRST[1:0],HRST[9:8],HRED[9:8],VRST[9],VRED[9] value being filled, it's always be 00b. No matter HRED[1:0] value being filled, it's always be 11b.</p> <p>Gates scan both inside and outside of the partial window.</p> | | | | | | | | | | | Name | Description | HRST[9:2] | Horizontal start address | HRED[9:2] | Horizontal end address. HRED must be greater than HRST. | VRST[9:0] | Vertical start address. | VRED[9:0] | Vertical end address. VRED must be greater than VRST. | PMODE |
| Name | Description | | | | | | | | | | | | | | | | | | | | | |
| HRST[9:2] | Horizontal start address | | | | | | | | | | | | | | | | | | | | | |
| HRED[9:2] | Horizontal end address. HRED must be greater than HRST. | | | | | | | | | | | | | | | | | | | | | |
| VRST[9:0] | Vertical start address. | | | | | | | | | | | | | | | | | | | | | |
| VRED[9:0] | Vertical end address. VRED must be greater than VRST. | | | | | | | | | | | | | | | | | | | | | |
| PMODE | 0: disable partial mode(default) 1: enable partial mode | | | | | | | | | | | | | | | | | | | | | |
| Restriction | | | | | | | | | | | | | | | | | | | | | | |

| R90H | Bit | | | | | | | | | | |
|-----------|-----|------|----|----|----|----|----|----|----|----|------|
| Inst/Para | R/W | D/CX | D7 | D6 | D5 | D4 | D3 | D2 | D1 | D0 | Code |
| PGM | W | 0 | 1 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 90H |

NOTE: "-" Don't care. can be set to VDD or GND level

| | | | | | | | | | | | |
|-------------|--|--|--|--|--|--|--|--|--|--|--|
| Description | -The command define as follows: After this command is issued, the chip would enter the program mode. The mode would return to standby by hardware reset. | | | | | | | | | | |
| Restriction | | | | | | | | | | | |



| R91H | Bit | | | | | | | | | | |
|-----------|-----|------|----|----|----|----|----|----|----|----|------|
| Inst/Para | R/W | D/CX | D7 | D6 | D5 | D4 | D3 | D2 | D1 | D0 | Code |
| APG | W | 0 | 1 | 0 | 0 | 1 | 0 | 0 | 0 | 1 | 91H |

NOTE: "-" Don't care. can be set to VDD or GND level

| | | | | | | | | | | | |
|-------------|---|--|--|--|--|--|--|--|--|--|--|
| Description | -The command define as follows: After this command is transmitted, the programming state machine would be activated. | | | | | | | | | | |
| Restriction | The BUSY flag would change state from 0 to 1 while the programming is completed. | | | | | | | | | | |

| R92H | Bit | | | | | | | | | | |
|--|-----|------|--------------------------------------|----|----|----|----|----|----|----|------|
| Inst/Para | R/W | D/CX | D7 | D6 | D5 | D4 | D3 | D2 | D1 | D0 | Code |
| RMTP | W | 0 | 1 | 0 | 0 | 1 | 0 | 0 | 1 | 0 | 92H |
| 1 st Parameter | R | 1 | Dummy | | | | | | | | - |
| 2 nd Parameter | R | 1 | The data of address 0x000 in the MTP | | | | | | | | - |
| 3 rd Parameter | R | 1 | The data of address 0x001 in the MTP | | | | | | | | - |
| 4 th Parameter | R | 1 | : | | | | | | | | - |
| 5 th Parameter | R | 1 | The data of address (n-1) in the MTP | | | | | | | | - |
| 6 th ~(m-1) th Parameter | R | 1 | | | | | | | | | - |
| m th Parameter | R | 1 | The data of address (n) in the MTP | | | | | | | | - |

NOTE: "-" Don't care. can be set to VDD or GND level

| | |
|--------------------|--|
| <p>Description</p> | <p>-The command define as follows: The command is used for reading the content of MTP for checking the data of programming. The value of (n) is depending on the amount of programmed data, the max address = 0x17FF</p>  <pre> graph TD RA2h[RA2h] --> R90h[Into Program Mode (R90h)] R90h --> R10h[Write Data (R10h)] R10h -- "Apply VMTP=10.1v" --> R91h[Activate program (R91h)] R91h -- "Check Busy_N=1, then remove VMTP" --> R92h[RMTP(R92h)] R92h --> Correct{Correct?} Correct -- Fail --> Reset[Reset] Correct -- Pass --> Finished[Finished, reset] Reset --> RA2h </pre> <p>The sequence of programming MTP(External power)</p> |
| <p>Restriction</p> |  <pre> graph TD Init["R4Dh=78 RA2h R00h=0F,A9 R01h=0F,00,47,47,47"] --> R90h[Into Program Mode (R90h)] R90h --> R10h[Write Data (R10h)] R10h --> R04h[PON(R04h)] R04h -- "Check Busy_N=1, delay 50ms" --> R91h[Activate program (R91h)] R91h -- "Check Busy_N=1" --> R92h[RMTP(R92h)] R92h --> Correct{Correct?} Correct -- Fail --> Reset[Reset] Correct -- Pass --> Finished[Finished, reset] Reset --> Init </pre> <p>The sequence of programming MTP(Internal power)</p> <p>This command only activates when BUSY_N = "1".</p> |

| R9FH | Bit | | | | | | | | | | |
|-----------------------------|-----|------|---------------------------------------|----|----|----|----|----|----|----|------|
| Inst/Para | R/W | D/CX | D7 | D6 | D5 | D4 | D3 | D2 | D1 | D0 | Code |
| RMRB | W | 0 | 1 | 0 | 0 | 1 | 1 | 1 | 1 | 1 | 9FH |
| 1 st Parameter | R | 1 | Dummy | | | | | | | | 00h |
| 2 nd Parameter | R | 1 | The data of address 0x16F7 in the MTP | | | | | | | | 00h |
| 3 rd Parameter | R | 1 | : | | | | | | | | 00h |
| : | R | 1 | : | | | | | | | | 00h |
| 97 th Parameter | R | 1 | : | | | | | | | | 00h |
| 98 th Parameter | R | 1 | : | | | | | | | | 00h |
| 101 th Parameter | R | 1 | The data of address 0x175A in the MTP | | | | | | | | 00h |

| | |
|-------------|---|
| Description | -The command define as follows: The command is used for reading the content of MTP Reserved Byte for checking the data of programming. This command could read these information from MTP directly. |
| Restriction | |

| RE3H | Bit | | | | | | | | | | |
|---------------------------|-----|------|-------------|----|----|----|-----------|----|----|----|------|
| Inst/Para | R/W | D/CX | D7 | D6 | D5 | D4 | D3 | D2 | D1 | D0 | Code |
| PWS | W | 0 | 1 | 1 | 1 | 0 | 0 | 0 | 1 | 1 | E3H |
| 1 st Parameter | W | 1 | VCOM_W[3:0] | | | | SD_W[3:0] | | | | 00h |

NOTE: "-" Don't care, can be set to VDD or GND level

- This command is set for saving power during refreshing period. If the output voltage of VCOM / Source is from negative to positive or from positive to negative, the power saving mechanism will be activated. The active period width is defined by the following two parameters.

VCOM_W: VCOM power saving width (unit = line period)

SD_W: Source power saving width (unit = 500nS), SD_W ≤ S2G

| RE4H | Bit | | | | | | | | | | |
|---------------------------|-----|------|----|----|----|----|----|----|--------------|----|------|
| Inst/Para | R/W | D/CX | D7 | D6 | D5 | D4 | D3 | D2 | D1 | D0 | Code |
| LVSEL | W | 0 | 1 | 1 | 1 | 0 | 0 | 1 | 0 | 0 | E4H |
| 1 st Parameter | W | 1 | - | - | - | - | - | - | LVD_SEL[1:0] | | 03h |

NOTE: "-" Don't care, can be set to VDD or GND level

| Description | LVD_SEL[1:0]: Low Power Voltage Selection | | | | | | | | | | |
|--------------|---|--------------|-----------|----|---------|----|---------|----|---------|----|-------------------|
| | <table border="1"> <thead> <tr> <th>LVD_SEL[1:0]</th> <th>LVD value</th> </tr> </thead> <tbody> <tr> <td>00</td> <td>< 2.2 V</td> </tr> <tr> <td>01</td> <td>< 2.3 V</td> </tr> <tr> <td>10</td> <td>< 2.4 V</td> </tr> <tr> <td>11</td> <td>< 2.5 V (default)</td> </tr> </tbody> </table> | LVD_SEL[1:0] | LVD value | 00 | < 2.2 V | 01 | < 2.3 V | 10 | < 2.4 V | 11 | < 2.5 V (default) |
| LVD_SEL[1:0] | LVD value | | | | | | | | | | |
| 00 | < 2.2 V | | | | | | | | | | |
| 01 | < 2.3 V | | | | | | | | | | |
| 10 | < 2.4 V | | | | | | | | | | |
| 11 | < 2.5 V (default) | | | | | | | | | | |
| Restriction | | | | | | | | | | | |

8. Handling, Safety and Environment Requirements


| Warning | |
|--|--|
| <p>The display glass may break when it is dropped or bumped on a hard surface. Handle with care. Should the display break, do not touch the electrophoretic material. In case of contact with electrophoretic material, wash with water and soap.</p> | |
| Caution | |
| <p>The display module should not be exposed to harmful gases, such as acid and alkali gases, which corrode electronic components. Disassembling the display module.</p> <p>Disassembling the display module can cause permanent damage and invalidates the warranty agreements.</p> <p>Observe general precautions that are common to handling delicate electronic components. The glass can break and front surfaces can easily be damaged. Moreover the display is sensitive to static electricity and other rough environmental conditions.</p> | |
| Data sheet status | |
| Product specification | This data sheet contains final product specifications. |
| Limiting values | |
| <p>Limiting values given are in accordance with the Absolute Maximum Rating System (IEC 134). Stress above one or more of the limiting values may cause permanent damage to the device. These are stress ratings only and operation of the device at these or at any other conditions above those given in the Characteristics sections of the specification is not implied. Exposure to limiting values for extended periods may affect device reliability.</p> | |
| Application information | |
| <p>Where application information is given, it is advisory and does not form part of the specification.</p> | |

9. Reliability test

| NO | Test items | Test condition |
|----|---|--|
| 1 | Low-Temperature Storage | T = -25°C, 240 h Test in white pattern |
| 2 | High-Temperature Storage | T=60° C, RH=35%, 240h Test in white pattern |
| 3 | High-Temperature Operation | T=40° C, RH=35%, 240h |
| 4 | Low-Temperature Operation | T=0° C, 240h |
| 5 | High-Temperature, High-Humidity Operation | T=40° C, RH=80%, 240h |
| 6 | High Temperature, High Humidity Storage | T=50° C, RH=90%, 240h Test in white pattern |
| 7 | Temperature Cycle | 1 cycle:[-25°C 30min]→[+60°C 30 min] : 50 cycles Test in white pattern |
| 8 | UV exposure Resistance | 765W/m ² for 168hrs,40 °C Test in white pattern |
| 9 | ESD Gun | Air+/-15KV;Contact+/-8KV (Test finished product shell, not display only) Air+/-8KV;Contact+/-6KV (Naked EPD display, no including IC and FPC area) Air+/-4KV;Contact+/-2KV (Naked EPD display, including IC and FPC area) |

Note: Put in normal temperature for 1hour after test finished, display performance is ok.

10. Typical Application Circuit



| Part Name | Requirements for spare part |
|-----------|--|
| C1—C12 | 0603/0805; X5R/X7R; Voltage Rating: ≥25V |
| R1、R2 | 0603/0805; 1% variation, ≥0.05W |
| D1—D3 | MBR0530: 1)Reverse DC Voltage ≥30V 2)Io ≥500mA 3)Forward voltage ≤430mV |
| Q1 | Si1308EDL: 1)Drain-Source breakdown voltage ≥30V 2)Vgs(th) ≤1.5V 3)Rds(on) ≤400mΩ |
| L1 | refer to NR3015: Io=500mA(max) |
| P1 | 24pins, 0.5mm pitch |

11. Matched Development Kit

Our Development Kit designed for SPI E-paper Display aims to help users to learn how to use E-paper Display more easily. It can refresh black-white E-paper Display, three-color (black, white and red/Yellow) E-paper Display and four-color(black, white, red and yellow) Good Display `s E-paper Display. And it is also added the functions of USB serial port, FLASH chip, font chip, current detection ect.

Development Kit consists of the development board and the pinboard.

Supported development platforms include STM32, ESP32, ESP8266, Arduino UNO, etc. More details, please click to the following links:

STM32 <https://www.good-display.com/product/219.html>

ESP32 <https://www.good-display.com/product/338.html>

ESP8266 <https://www.good-display.com/product/220.html>


Arduino UNO <https://www.good-display.com/product/222.html>

GOODDISPLAY

12. Inspection method and condition

12. 1 Inspection condition


| Item | Condition |
|-------------------|-----------------------------|
| Illuminance | 800~1500 lux |
| Temperature | 22℃ ± 3℃ |
| Humidity | 55 ± 10 %RH |
| Distance | ≥30cm |
| Angle | Vertical fore and aft 45 |
| Inspection method | By eyes |




12. 2 Zone definition

- A Zone: Active area
- B Zone: Border zone
- C Zone: From B zone edge to panel edge

基板边缘



| Inspection item | | Figure | Inspection standard | Inspection method | MAJ / MIN |
|----------------------------|---------------------|---|---|-------------------|-----------|
| PS defect | Water proof film |  | 1. Waterproof film damage, wrinkled, open edge, not allowed 2. Exceeding the edge of module (according to the lamination drawing) Not allowed 3. Edge warped exceeds height of technical file, not allowed | Check by eyes | MIN |
| RTV defect | Adhesive effect |  | Adhesive height exceeds the display surface, not allowed 1. Overflow, exceeds the panel side edge, affecting the size, not allowed 2. No adhesive at panel edge $\leq 1\text{mm}$, no exposure of wiring, allowed 3. No adhesive at edge and corner $1*1\text{mm}$, no exposure of wiring, allowed Protection adhesive, coverage width within $W \leq 1.5\text{mm}$, no break of adhesive, allowed | Check by eyes | MIN |
| | Adhesive re-fill | | Dispensing is uniform, without obvious concave and breaking, bubbling and swell, not higher than the upper surface of the PS, and the diameter of the adhesive re-filling is not more than 8mm, allowed | Check by eyes | MIN |
| EC defect | Adhesive bubble |  | 1. Effective edge sealing area of hot melt products $\geq 1/2$ edge sealing area; 2. Bubble $a+b \geq 1/2$ effective width, $N \leq 3$, spacing $\geq 5\text{mm}$, allowed No exposure of wiring, allowed | Check by eyes | MIN |
| Inspection item | | Figure | Inspection standard | Inspection method | MAJ / MIN |
| EC defect | Adhesive effect |  | 1. Overflow, exceeds the panel side edge, affecting the size, not allowed 2. No adhesive at panel edge $\leq 1\text{mm}$, no exposure of wiring, allowed 3. No adhesive at edge and corner $1*1\text{mm}$, no exposure of wiring, allowed 4. Adhesive height exceeds the display surface, not allowed | Visual, caliper | MIN |
| Silver dot adhesive defect | Silver dot adhesive | | 1. Single silver dot dispensing amount $\geq 1\text{mm}$, allowed 2. One of the double silver dot dispensing amount is $\geq 1\text{mm}$ and the other has adhesive (no reference to 1mm) Allowed | Visual | MIN |
| | | | Silver dot dispensing residue on the panel $\leq 0.2\text{mm}$, allowed | Film gauge | MIN |
| FPC defect | FPC wiring |  | FPC, TCP damage / gold finger peroxidation, adhesive residue, not allowed | Visual | MIJ |
| | FPC golden finger | | The height of burr edge of TCP punching surface $\cong 0.4\text{mm}$, not allowed | Caliper | MIN |
| | FPC damage/cr ease |  | Damage and breaking, not allowed Crease does not affect the electrical performance display, allowed | Check by eyes | MIN |

| Inspection item | | Figure | Inspection standard | Inspection method | MAJ/ MIN |
|------------------------|-------------------------|---|---------------------|----------------------------------|-------------|
| Protective film defect | Protective film | Scratch and crease on the surface but no affect to protection function, allowed | | Check by eyes | MIN |
| | | Adhesive at edge $L \leq 5\text{mm}$, $W \leq 0.5\text{mm}$, $N=2$, no entering into viewing area | | Check by eyes | MIN |
| Stain defect | Stain | If stain can be normally wiped clean by $> 99\%$ alcohol, allowed | | Visual | MIN |
| Pull tab defect | Pull tab | The position and direction meet the document requirements, and ensure that the protective film can be pulled off. | | Check by eyes/ Manual pulling | MIN |
| Shading tape defect | Shading tape | Tilt $\leq 10^\circ$, flat without warping, completely covering the IC. | | Check by eyes/ Film gauge | MIN |
| Stiffener | Stiffener | Flat without warping, Exceeding the left and right edges of the FPC is not allowed. Left and right can be less than 0.5mm from FPC edge | | Check by eyes | MIN |
| Label | Label/ Spraying code | The content meets the requirements of the work sheet. The attaching position meets the requirements of the technical documents. | | Check by eyes | MIN |


GOODDISPLAY

13. Packaging


| | | |
|-----------------------------|-------------------------|------------------|
| <i>CUSTOMER'S APPROVED:</i> | <i>DATE: 2023.02.06</i> | <i>PAGE: 1/1</i> |
|-----------------------------|-------------------------|------------------|

PACKLING ORDER:


1) Putting 20 pcs Modules on each PET tray. Product with EPE pad on top.




2) Putting 18 pcs PET trays together with 1 empty tray on the top of PET tray. the tray together with rubber band.




3) Insert in the ESD bag, add desiccant in the ESD bag. Plastic sealing.



4) Inside the outer box, The box is filled with EPE pad from top to bottom, front to back.



5) Packing finished



Note: 20x(19-1)=360pcs/Outcarton
Dimension (Out carton): 500*350*200mm

| | | |
|------|------|------|
| Drw: | Chk: | Apv: |
|------|------|------|

14. Precautions

- (1) Do not apply pressure to the EPD panel in order to prevent damaging it.
- (2) Do not connect or disconnect the interface connector while the EPD panel is in operation.
- (3) Do not touch IC bonding area. It may scratch TFT lead or damage IC function.
- (4) Please be mindful of moisture to avoid its penetration into the EPD panel, which may cause damage during operation.
- (5) If the EPD Panel / Module is not refreshed every 24 hours, a phenomena known as "Ghosting" or "Image Sticking" may occur. It is recommended to refreshed the ESL /EPD Tag every 24 hours in use case. It is recommended that customer ships or stores the ESL / EPD Tag with a completely white image to avoid this issue
- (6) High temperature, high humidity, sunlight or fluorescent light may degrade the EPD panel's performance. Please do not expose the unprotected EPD panel to high temperature, high humidity, sunlight, or fluorescent for long periods of time.
- (7) For more precautions, please click on the link:
<https://www.good-display.com/news/80.html>

GOODDISPLAY